

HIKVISION PRODUCT CATALOGUE

2016/17



	Page
Naming Rule	4
Analogue Camera Comparison Chart	7
Turbo HD Cameras.....	7
Turbo HD PTZs	11
Turbo 3.0 DVRs	12
IP Cameras	16
IP PTZ Cameras.....	25
NVR Comparison Chart.....	27
NVRs.....	27
Blazer NVRs	33
Encoders.....	33
Decoders	34
Keyboards	37
Monitors & Large Screens	38
Video Intercom.....	40
Brackets	42
Ancillaries.....	48
Notes	49

NVR Naming Rule

1	2	3	4	5	6	7	8
DS-	76	08	N	I	-E	2	/8P
↓	↓	↓	↓	↓	↓	↓	↓
DS-: Hikvision Products	Product Series	The number of IP channels	NVR	"I": stands for International	Stands for the product generation no.	The number of HDDs	Extended function and features
DS-: General Products iDS-: Intelligent products	NVR: 71/76/77/86/96	Range from 01 to 256	N: NVR	With I: for International markets Without I: for domestic markets only	New generation: -E/F/G/H/I/K Old generation: -ST/-RT	Range from 1 to 24	/xP: built-in PoE switch ports, x stands for the number of ports /W: WIFI /A: All in one /GS /GW /GE: 3G /GLT /GLF: 4G /L: LCD /H: with extended HDMI interfaces /I: with extended intelligent motherboard
Examples:							
DS-9664NI-I8	Hikvision NVR, 64-ch IP video inputs, 8x HDDs						
DS-96256NI-F24/H	Hikvision NVR, 256-ch IP video inputs, 24 HDDs, with extended HDMI interfaces						

DVR Naming Rule

1	2	3	4	5	6	7	8
DS-	72	08	HUH	I	-F	2	/N
↓	↓	↓	↓	↓	↓	↓	↓
DS-: Hikvision Products	Product Series	Analogue Channel No.	Stands for the real-time encoding resolution of DVR	"I": stands for International	Stands for the product generation no.	Supported hard drive no.	Extended function and features
DS-: General Products iDS-: Intelligent products	DVR: 72/73/81/90	Range from 01 to 32	HGH:720p HQH:1080p HUH:3MP/5MP	With I: for International markets Without I: for domestic markets only	New generation: -F Old generation: -SH	Range from 1 to 8	/N: non-real-time
Example:							
DS-7204HUHI-F1/N	Hikvision TVI DVR, 4-ch Analogue video input, up to 3MP/5MP non-real-time encoding, 2 HDD interfaces						

PTZ Cameras

DS-2	D	F	8	2	30	I	V	—	AE	L
↓	↓	↓	↓	↓	↓	↓	↓		↓	↓
DS-2: Hikvision front-end product	A: Analogue D: Network	F: High Level E: Entry Level	The size of PTZ camera: 2: 2.5" 4: 4" 5: 5" 6: 6" 7: 7" 8: 8"	Resolution: 0: 700TVL or WD1 1: 1.3MP 2: 2MP 3: 3MP 4: 4MP 5: 5MP 6: 6MP 8: 8MP	Optical Zoom: 03: 3x optical 04: 4x optical 12: 12x optical 18: 18x optical 20: 20x optical 23: 23x optical 30: 30x optical 36: 36x optical	Default: without IR I: with IR light I3: 300m laser IR I5: 500m laser IR	V: R4 series W: R7 Series		A: 24VAC D: 12VDC E: PoE/PoE+/ Hi-PoE	L: Low temperature model
Example:										
DS-2DF8223I-AEL 2MP, 23x Hikvision, 8", IR, network high PTZ Dome (24VAC, P/N system adaptive, RJ45, outdoor PTZ Dome)										

Model Name Coding Rule



IP Cameras

DS-2	C	D	2	0	1	2		—	I
↓	↓	↓	↓	↓	↓	↓	↓		↓
DS-2: Hikvision front-end product iDS-2: Hikvision intelligent camera	Colour TD: Thermal	IP camera	2: 2 line camera, entry level 4: 4 line camera, project level 6: 6 line camera, vehicle/special market	Different appearance Even: box/bullet/cube/covert Odd: dome/turret A: Bullet C: Cube/panda D: Pinhole E: Recessed-mount mini dome F: PT Dome Q: PT camera T: EXIR Bullet	0: lower than 1MP 1: 1MP/1.3MP/1.4MP 2: 2MP 3: 3MP 4: 4MP 5: 5MP 6: 6MP 8: 8MP C: 12MP	Different Platform/Chipset B: BNC output (some cameras without "B" also support CVBS output) I: support IR Z: motorised lens PT: with pan and tilt H: heater W: support WIFI GS/GW/GE: support 3G GLT/GLF: support 4G S: audio, alarm and 485 interface (some cameras with "-S" have RS485 interface, some cameras without "S" also have audio and alarm interfaces) A: ABF P: P-iris SDI: HD-SDI output FC: Fibre optical output FCB: Fibre optical digital output (without compression) M: HDMI output 65: -IO: 5.5mm power interface & RJ45 network interface -I: molex power interface & aviation network interface iDS: /B: Behaviour; /F: Face recognition; /H: Heat map; /C: People counting	D: DC power supply only F: SD/SDHC FWD: WDR, SD/SDHC H: High frame rate		

Example:
DS-2CD2742FWD-IS New generation, entry level 4MP Dome IP camera (PoE, support IR, Alarm in/out, True WDR)

Analogue Cameras

DS-2	C	E	1	6	D	5	T	—	IT3
DS-2: Hikvision front-end product	Colour	E: Entry Level	1: Box/bullet 5: Dome/mini	6: 2nd generation product	C: 720p D: 1080p F: 3MP	5: Turbo Camera with dual outputs 1: Turbo Camera with single output	T: Turbo Analogue HD		H: heater VF: varifocal VP: vandal-proof IR: IR range: 10-20m IRP: IR range: 10-20m (plastic) IR3: IR range: 30-40m IR5: IR range: 50-60m IRA: IR range: 100-110m IT3: EXIR: 30-40m ITS: EXIR: 50-80m A: 24VAC and 12VDC C: 100VAC-240V Z: Motorised lens (Turbo HD Camera)

The Hikvision logo is displayed in a bold, sans-serif font. The word 'HIK' is in red, and 'VISION' is in black.A large, stylized speedometer graphic with a black face and white markings. The needle is red and points towards the top right. The text 'TURBO HD 3.0' is written in large, bold, red letters across the top of the speedometer. Below it, in smaller white text, are the specifications: '4K Output / 5MP Input', '1200m Transmission', and 'H.264+ Smart Codec'. The background of the top half of the advertisement features a red sports car with flames around its wheel and a dark, cloudy sky.

4K Output / 5MP Input

1200m Transmission

H.264+ Smart Codec



TURBO HD

Rev Up Analogue with Turbo HD over Coax

Hikvision's Turbo HD 3.0 Solution

Adding turbo to your engine improves power, performance, and efficiency. Now, the highly compatible Turbo HD 3.0 Solution by Hikvision gives security systems that same boost – whether you install Turbo 3.0 cameras, DVRs, or the whole solution. How does it work? Turbo 3.0 technology uses coaxial cables to transmit video and power, raises video performance up to 4K, and improves bandwidth efficiency by 50%. Turbo-boost surveillance systems of any size – with Hikvision.

- Higher video performance with up to 5MP HDTVI camera input & 4K video output
- Higher calibre H.264+ compression improves encoding efficiency by up to 50% and reduces data storage costs
- Longer transmission distances at up to 1200m for HD270p over coaxial cable – a 240% increase!



Hikvision UK
4 The Square,
Stockley Park, Uxbridge, UB11 1ET
Tel: 01628 902140
sales.uk@hikvision.com
support.uk@hikvision.com

www.hikvision.com

Turbo HD Analogue Camera Comparison Chart

PRODUCT SERIES	D7T	D5T	F1T	F7T
RESOLUTION	1080p	1080p	3MP	3MP
DNR	✓	✓	✓	✓
3D DNR		✓		✓
TRUE WDR	✓	✓		✓
EXIR	✓	(-IT)	✓	(-IT)
LOW-LIGHT	0.01	0.01	0.01	0.01
DIP SWITCH		✓		✓
OSD MENU	✓	✓	✓	✓
DUAL OUTPUT (TVI/CVBS)		✓		
MOTORISED LENS	✓	✓		✓
HLC				
HEATER		✓		
SMART FOCUS		✓		
DEFOG		✓		
REMOTE UPGRADE	✓		✓	✓

DS-2CE16D5T-AVFIT3

TURBO HD 1080P VARIFOCAL EXIR BULLET CAMERA



- HD 1080p Video
- Lens 2.8-12mm
- Adopt HDTVI Technology
- EXIR illumination up to 50m
- DNR, Smart IR, True WDR
- Outdoor ready IP66
- OSD menu
- Power 12VDC $\pm$ 15%, 24VAC $\pm$ 15% DC Max. 10W

Bracket(s): DS-1275ZJ DS-1260ZJ DS-1280ZJ-S

PART NO.	QUICK REF.
DS-2CE16D5T-AVFIT3(2.8-12MM)	0782280

DS-2CE56D5T-IRM

HD 1080P IR TURRET CAMERA



- HD 1080p Video
- Lens options: 2.8mm, 3.6mm, 6mm
- Adopt HDTVI Technology
- IR illumination up to 20m
- DNR, Smart IR, True WDR
- Outdoor ready IP66
- OSD menu
- Power 12VDC Max. 4W

Bracket(s): DS-1272ZJ-110-TRS DS-1275ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CE56D5T-IRM(2.8MM)	0786390
DS-2CE56D5T-IRM(3.6MM)	0786400
DS-2CE56D5T-IRM(6MM)	0786410

DS-2CE56D5T-IT3

HD 1080P EXIR TURRET CAMERA



- HD 1080p Video
- Lens options: 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR
- Outdoor ready IP66
- OSD menu
- Power 12VDC Max. 5W

Bracket(s): DS-1272ZJ-110 DS-1275ZJ DS-1276ZJ DS-1280ZJ-S DS-1258ZJ DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56D5T-IT3(2.8MM)	0786420
DS-2CE56D5T-IT3(3.6MM)	0782340
DS-2CE56D5T-IT3(6MM)	0786430
DS-2CE56D5T-IT3(8MM)	0786440
DS-2CE56D5T-IT3(12MM)	0786450
DS-2CE56D5T-IT3(16MM)	0786460

DS-2CE56D5T-VFIT3

HD 1080P VARIFOCAL EXIR TURRET CAMERA



- HD 1080p Video
- Lens: 2.8~12mm Varifocal
- Adopt HDTVI Technology
- EXIR illumination up to 50m
- DNR, Smart IR, True WDR
- Outdoor ready IP66
- OSD menu
- Power 12VDC Max. 7W

Bracket(s): DS-1273ZJ-130-TRL DS-1275ZJ
DS-1276ZJ DS-1280ZJ-M DS-1281ZJ-M

PART NO.	QUICK REF.
DS-2CE56D5T-VFIT3(2.8-12MM)	0782350

DS-2CE16D7T-IT3Z

HD 1080P MOTORISED VF EXIR BULLET CAMERA



- HD 1080p Video
- Lens: 2.8~12mm
- Adopt HDTVI Technology
- IR illumination up to 40m
- DNR, Smart IR, True WDR
- Outdoor IP66
- Power 12VDC Max. 6W

Bracket(s): DS-1275ZJ DS-1280ZJ-S

PART NO.	QUICK REF.
DS-2CE16D7T-IT3Z(2.8-12MM)	0782290

DS-2CE16D7T-IT3

HD 1080P WDR EXIR BULLET CAMERA



- HD 1080p Video
- Lens options: 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12 VDC Max. 5W

Bracket(s): DS-1280ZJ-S

PART NO.	QUICK REF.
DS-2CE16D7T-IT3(2.8MM)	0786470
DS-2CE16D7T-IT3(3.6MM)	0782300
DS-2CE16D7T-IT3(6MM)	0786480
DS-2CE16D7T-IT3(8MM)	0786490
DS-2CE16D7T-IT3(12MM)	0786500
DS-2CE16D7T-IT3(16MM)	0786510

DS-2CE56D7T-IT3

HD 1080P WDR EXIR TURRET CAMERA



- HD 1080p Video
- Lens options: 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC Max. 5W

Bracket(s): DS-1273ZJ-130-TRL DS-1275ZJ
DS-1276ZJ DS-1280ZJ-M DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56D7T-IT3(2.8MM)	0782380
DS-2CE56D7T-IT3(3.6MM)	0782390
DS-2CE56D7T-IT3(6MM)	0786520
DS-2CE56D7T-IT3(8MM)	0786530
DS-2CE56D7T-IT3(12MM)	0786540
DS-2CE56D7T-IT3(16MM)	0786550

DS-2CE56D7T-ITM

HD 1080P WDR EXIR TURRET CAMERA



- HD 1080p Video
- Lens options: 2.8mm, 3.6mm, 6mm
- Adopt HDTVI Technology
- EXIR illumination up to 20m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC Max. 5W

Bracket(s): DS-1272ZJ-110 DS-1275ZJ
DS-1276ZJ DS-1280ZJ-S DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56D7T-ITM(2.8MM)	0782370
DS-2CE56D7T-ITM(3.6MM)	0786560
DS-2CE56D7T-ITM(6MM)	0786570

DS-2CE16F1T-IT

3MP EXIR BULLET CAMERA



- 3MP Video
- Lens options: 2.8mm, 3.6mm, 6mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 20m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CE16F1T-IT(2.8MM)	0789280
DS-2CE16F1T-IT(3.6MM)	0789290
DS-2CE16F1T-IT(6MM)	0789300

DS-2CE16F1T-IT1 3MP EXIR BULLET CAMERA



- 3MP Video
- Lens: 2.8mm, 3.6mm, 6mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 20m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CE16F1T-IT1(2.8MM)	0786580
DS-2CE16F1T-IT1(3.6MM)	0786590
DS-2CE16F1T-IT1(6MM)	0786600

DS-2CE16F1T-IT3 3MP EXIR BULLET CAMERA



- 3MP Video
- Lens: 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CE16F1T-IT3(2.8MM)	0786610
DS-2CE16F1T-IT3(3.6MM)	0786620
DS-2CE16F1T-IT3(6MM)	0786630
DS-2CE16F1T-IT3(8MM)	0786640
DS-2CE16F1T-IT3(12MM)	0786650
DS-2CE16F1T-IT3(16MM)	0786660

DS-2CE16F1T-IT5 3MP EXIR BULLET CAMERA



- 3MP Video
- Lens: 3.6mm, 6mm, 8mm, 12mm, 16mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 80m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CE16F1T-IT5(3.6MM)	0786670
DS-2CE16F1T-IT5(6MM)	0786680
DS-2CE16F1T-IT5(8MM)	0786690
DS-2CE16F1T-IT5(12MM)	0786700
DS-2CE16F1T-IT5(16MM)	0786710

DS-2CE56F1T-IT1 3MP EXIR TURRET CAMERA



- 3MP Video
- Lens: 2.8mm, 3.6mm, 6mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 20m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1275ZJ DS-1276ZJ
DS-1280ZJ-S DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56F1T-IT1(2.8MM)	0786720
DS-2CE56F1T-IT1(3.6MM)	0786730
DS-2CE56F1T-IT1(6MM)	0786740

DS-2CE56F1T-IT3 3MP EXIR TURRET CAMERA



- 3MP Video
- Lens: 2.8mm, 3.6mm, 6mm, 8mm, 12mm, 16mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1275ZJ DS-1276ZJ
DS-1280ZJ-S DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56F1T-IT3(2.8MM)	0786750
DS-2CE56F1T-IT3(3.6MM)	0786760
DS-2CE56F1T-IT3(6MM)	0786770
DS-2CE56F1T-IT3(8MM)	0786780
DS-2CE56F1T-IT3(12MM)	0786790
DS-2CE56F1T-IT3(16MM)	0786800

DS-2CE56F1T-ITM 3MP EXIR TURRET CAMERA



- 3MP Video
- Lens: 2.8mm, 3.6mm, 6mm optional
- Adopt HDTVI Technology
- EXIR illumination up to 20m
- DNR, Smart IR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS DS-1275ZJ
DS-1276ZJ DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56F1T-ITM(2.8MM)	0786810
DS-2CE56F1T-ITM(3.6MM)	0786820
DS-2CE56F1T-ITM(6MM)	0786830

DS-2CE16F7T-IT5

3MP WDR EXIR BULLET CAMERA



- 3MP Video
- Lens options: 3.6mm, 6mm, 8mm, 12mm, 16mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC 5W

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CE16F7T-IT5(3.6MM)	0786840
DS-2CE16F7T-IT5(6MM)	0786850
DS-2CE16F7T-IT5(8MM)	0786860
DS-2CE16F7T-IT5(12MM)	0786870
DS-2CE16F7T-IT5(16MM)	0786880

DS-2CE56F7T-ITZ

3MP MOTORISED VF EXIR DOME CAMERA



- 3MP Video
- Lens: 2.8~12mm
- Adopt HDTVI Technology
- EXIR illumination up to 30m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC 4.5W

Bracket(s): DS-1275ZJ DS-1273ZJ-130
DS-1276ZJ DS-1271ZJ-130
DS-1273ZJ-130B DS-1249ZJ

PART NO.	QUICK REF.
DS-2CE56F7T-ITZ(2.8-12MM)	0782400

DS-2CE16F7T-IT3Z

3MP MOTORISED VF EXIR BULLET CAMERA



- 3MP Video
- Lens: 2.8~12mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC Max. 6W

Bracket(s): DS-1275ZJ DS-1280ZJ-S

PART NO.	QUICK REF.
DS-2CE16F7T-IT3Z(2.8-12MM)	0782310

DS-2CE56F7T-VPIT3Z

3MP MOTORISED VF PROOF EXIR DOME CAMERA



- 3MP Video
- Lens: 2.8~12mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC Max. 4.5W

Bracket(s): DS-1273ZJ-140 DS-1275ZJ
DS-1276ZJ DS-1271ZJ-140
DS-1273ZJ-140B DS-1241ZJ DS-1240ZJ

PART NO.	QUICK REF.
DS-2CE56F7T-VPIT3Z (2.8-12MM)	0782410

DS-2CE56F7T-IT3Z

3MP MOTORISED VF EXIR TURRET CAMERA



- 3MP Video
- Lens: 2.8~12mm
- Adopt HDTVI Technology
- EXIR illumination up to 40m
- DNR, Smart IR, True WDR, OSD menu
- Outdoor IP66
- Power 12VDC 6W

Bracket(s): DS-1273ZJ-130-TRL DS-1275ZJ
DS-1276ZJ DS-1280ZJ-M DS-1281ZJ-S

PART NO.	QUICK REF.
DS-2CE56F7T-IT3Z (2.8-12MM)	0782420

DS-2AE4223TI-D

4" PTZ (23x) 1080P CAMERA WITH IR



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4-92mm
- 23× Optical zoom, 16× Digital zoom
- IR illumination up to 100m
- Digital Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- TurboHD and BNC output (TurboHD supports Control over Coax)
- Outdoor ready IP66
- RS485 Protocols: HIKVISION, Pelco-P, Pelco-D
- Power 12VDC Max. 18W

Bracket(s): DS-1602ZJ

PART NO.	QUICK REF.
DS-2AE4223TI-D	0788540

DS-2AE5223TI-A

5" PTZ (23x) 1080P CAMERA WITH IR



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4-92mm
- 23× Optical zoom, 16× Digital zoom
- IR illumination up to 150m
- Digital Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- TurboHD and BNC output (TurboHD supports Control over Coax)
- Outdoor ready IP66
- RS485 Protocols: HIKVISION, Pelco-P, Pelco-D
- Power 12VDC Max. 18W

Bracket(s): DS-1661ZJ DS-1662ZJ
DS-1663ZJ DS-1618ZJ DS-1660ZJ
DS-1602ZJ DS-1602ZJ-pole
DS-1602ZJ-corner DS-1602ZJ-box
DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2AE5223TI-A	0782070

DS-2AE7230TI-A

1080P PTZ (30x) CAMERA WITH IR



- Full HD resolution 1080p (1920 × 1080@25fps)
- Lens: 4.0-120mm
- 30x Optical zoom, 16x Digital zoom
- IR illumination up to 120m
- Digital Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- TurboHD and BNC output (TurboHD supports Control over Coax)
- Outdoor ready IP66
- RS-485 Protocols: HIKVISION, Pelco-P, Pelco-D
- 24VAC (for -A model) Max. 30W

Bracket(s): DS-1661ZJ DS-1662ZJ
DS-1663ZJ DS-1618ZJ DS-1660ZJ
DS-1602ZJ DS-1602ZJ-pole
DS-1602ZJ-corner DS-1602ZJ-box
DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2AE7230TI-A	0782080

DS-2AE4223T-A/A3

4" PTZ (23x) 1080P CAMERA WITHOUT IR



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4-92mm
- 23× Optical zoom, 16× Digital zoom
- Digital Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- TurboHD and BNC output (TurboHD supports Control over Coax)
- IP66 standard (outdoor dome)
- Self-adaptive to HIKVISION, Pelco-P/D protocol
- 24VAC, Outdoor dome: Max. 18W (Heater On), Max. 12W (Heater Off), Indoor dome: Max. 12W
- A: outdoor, A3: indoor

Bracket(s): DS-1602ZJ

PART NO.	QUICK REF.
DS-2AE4223T-A	0786890
DS-2AE4223T-A3	0786900

DS-2AE5230T-A/A3

5" PTZ (30x) 1080P CAMERA WITHOUT IR



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4-120mm
- 30× Optical zoom, 16× Digital zoom
- Digital Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- TurboHD and BNC output (TurboHD supports Control over Coax)
- IP66 standard (outdoor dome)
- Self-adaptive to HIKVISION, Pelco-P/D protocol
- 24VAC, Outdoor dome: Max. 20W (Heater On), Max. 12W (Heater Off), Indoor dome: Max. 12W
- A: outdoor, A3: indoor

Bracket(s): DS-1602ZJ

PART NO.	QUICK REF.
DS-2AE5230T-A	0786910
DS-2AE5230T-A3	0786920

DS-7204HQHI-F1/N/(A) 4 CHANNEL TURBO HD DVR



- 4 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 1-ch up to 2MP resolution
- Recording Resolution: 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF non-1080p lite mode: 1080p (non-real-time)/720p/VGA/WD1/4CIF/CIF
- Video Compression: H.264, H.264+
- 1 SATA interface
- 2× USB 2.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 15W
- 1U chassis (315×242×45mm)

PART NO.	QUICK REF.
DS-7204HQHI-F1/N	0782640
DS-7204HQHI-F1/N/A	0782490

DS-7208HQHI-F1/N/(A) 8 CHANNEL TURBO HD DVR



- 8 HD CVI/TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 2MP resolution
- Recording Resolution: 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF non-1080p lite mode: 1080p (non-real-time)/720p/VGA/WD1/4CIF/CIF
- Video Compression: H.264, H.264+
- 1 SATA interface
- 2× USB 2.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- /A: Alarm 8 input/4 output
- Power Supply: 12VDC ≤ 20W
- 1U chassis (315×242×45mm)

PART NO.	QUICK REF.
DS-7208HQHI-F1/N	0782650
DS-7208HQHI-F1/N/A	0782500

DS-7216HQHI-F1/N/(A) 16 CHANNEL TURBO HD DVR



- 16 HD CVI/TVI/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 2MP resolution
- Recording Resolution: 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF non-1080p lite mode: 1080p (non-real-time)/720p/VGA/WD1/4CIF/CIF
- Video Compression: H.264, H.264+
- 1 SATA interface
- 1 USB 2.0 Interface & 1 USB 3.0 Interface
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 30W
- 1U chassis (315×242×45mm)

PART NO.	QUICK REF.
DS-7216HQHI-F1/N	0782670
DS-7216HQHI-F1/N/A	0782540

DS-7208HQHI-F2/N/(A) 8 CHANNEL TURBO HD DVR



- 8 HD CVI/TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 2MP resolution
- When 1080p Lite mode not enabled: 1080p/720p/VGA/WD1/4CIF/CIF
- When 1080p Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
- Video Compression: H.264, H.264+
- 2 SATA interfaces
- 2× USB 2.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- /A: Alarm 8 input/4 output
- Power Supply: 12VDC ≤ 20W
- 380×320×48mm

PART NO.	QUICK REF.
DS-7208HQHI-F2/N	0782660
DS-7208HQHI-F2/N/A	0782510

DS-7216HQHI-F2/N/(A) 16 CHANNEL TURBO HD DVR



- 16 HD CVI/TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 2MP resolution
- When 1080p Lite mode not enabled: 1080p/720p/VGA/WD1/4CIF/CIF
- When 1080p Lite mode enabled: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
- Video Compression: H.264, H.264+
- 2 SATA interfaces
- Front panel: 1× USB 2.0
Rear panel: 1× USB 3.0
- 1 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 30W
- 380×320×48mm

PART NO.	QUICK REF.
DS-7216HQHI-F2/N	0782680
DS-7216HQHI-F2/N/A	0782550

DS-7304HQHI-F4/N 4 CHANNEL TURBO HD DVR



- 4 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input up to 6-ch up to 4MP resolution
- 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
- Non-1080p lite mode: 1080p (non-realtime)/720p (non-real-time)/VGA/WD1/4CIF/CIF
- H.264, H.264+
- 4 SATA interfaces
- 2× USB 2.0 & 1× USB 3.0
- 1 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

PART NO.	QUICK REF.
DS-7304HQHI-F4/N	0786930

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

Turbo 3.0 DVRs



DS-7308HQHI-F4/N 8 CHANNEL TURBO HD DVR



- 8 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: up to 10-ch up to 4MP resolution
- 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
Non-1080p lite mode: 1080p (non-realtime)/720p (non-real-time)/VGA/WD1/4CIF/CIF
- H.264, H.264+
- 4 SATA interfaces
- 2× USB 2.0 & 1× USB 3.0
- 1 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

PART NO.	QUICK REF.
DS-7308HQHI-F4/N	0786940

DS-7316HQHI-F4/N 16 CHANNEL TURBO HD DVR



- 16 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: up to 18-ch up to 4MP resolution
- 1080p lite mode: 1080p lite/720p lite/VGA/WD1/4CIF/CIF
Non-1080p lite mode: 1080p (non-realtime)/720p (non-real-time)/VGA/WD1/4CIF/CIF
- H.264, H.264+
- 4 SATA interfaces
- 2× USB 2.0 & 1× USB 3.0
- 1 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

PART NO.	QUICK REF.
DS-7316HQHI-F4/N	0786950

DS-7204HUHI-F1/N 4 CHANNEL TURBO HD DVR



- 4 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 4MP resolution
- 3 MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 1 SATA interface
- 2× USB 2.0
- 2 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080 resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 15W
- 1U chassis (315×242×45mm)

PART NO.	QUICK REF.
DS-7204HUHI-F1/N	0786960

DS-7208HUHI-F1/N 8 CHANNEL TURBO HD DVR



- 8 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 4MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 1 SATA interface
- Front panel: 1× USB 2.0
Rear panel: 1× USB 3.0
- 1 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI output at up to 4K (3840×2160) resolution, VGA output at up to 1920×1080 resolution
- /A: Alarm 8 input/4 output
- Power Supply: 12VDC ≤ 20W
- 1U chassis (315×242×45mm)

PART NO.	QUICK REF.
DS-7208HUHI-F1/N	0782520

DS-7204HUHI-F2/N 4 CHANNEL TURBO HD DVR



- 4 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 4MP resolution
- 3 MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 2 SATA interfaces
- 2× USB 2.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080 resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 15W
- 380×320×48mm

PART NO.	QUICK REF.
DS-7204HUHI-F2/N	0786990

DS-7208HUHI-F2/N 8 CHANNEL TURBO HD DVR



- 8 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 4MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 2 SATA interfaces
- 2× USB 2.0 & 1× USB 3.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- /A: Alarm 8 input/4 output
- Power Supply: 12VDC ≤ 20W
- 380×320×48mm

PART NO.	QUICK REF.
DS-7208HUHI-F2/N	0782530

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-7216HUHI-F2/N 16 CHANNEL TURBO HD DVR



- 16 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: 2-ch up to 4MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 2 SATA interfaces
- 2× USB 2.0 & 1× USB 3.0
- 1 RJ45 10m/100m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- /A: Alarm 4 input/1 output
- Power Supply: 12VDC ≤ 20W
- 380×320×48mm

DS-7304HUHI-F4/N 4 CHANNEL TURBO HD DVR



- 4 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: up to 6-ch up to 8MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 4 SATA interfaces
- Front panel: 2× USB 2.0
- Rear panel: 1× USB 3.0
- 2 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

DS-7308HUHI-F4/N 8 CHANNEL TURBO HD DVR



- 8 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: up to 10-ch up to 8MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 4 SATA interfaces
- Front panel: 2× USB 2.0
- Rear panel: 1× USB 3.0
- 2 RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

PART NO.	QUICK REF.
DS-7216HUHI-F2/N	0787020

PART NO.	QUICK REF.
DS-7304HUHI-F4/N	0787040

PART NO.	QUICK REF.
DS-7308HUHI-F4/N	0787050

DS-7316HUHI-F4/N 16 CHANNEL TURBO HD DVR



- 16 HD TVI/AHD/Analogue self-adaptive interfaces input
- IP video input: up to 18-ch up to 8MP resolution
- 3MP/1080p/720p/WD1/4CIF/VGA/CIF
- Video Compression: H.264, H.264+
- 4 SATA interfaces
- Front panel: 2× USB 2.0
- Rear panel: 1× USB 3.0
- 2, RJ45 10m/100m/1000m self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840×2160) resolution
- 100 to 240VAC
- 1.5U chassis (445×390×70mm)

PART NO.	QUICK REF.
DS-7316HUHI-F4/N	0788550



EASY IP SOLUTION MORE CHOICES FOR EVERY REQUIREMENT

For vigilant home and business owners, Hikvision offers a complete, professional-grade "Easy IP" video surveillance system that connects you to your entire property and gives you reassurance that it is safeguarded. This HD solution is easy to install, easy to connect, easy to store, and easy to view — allowing you to experience the true benefits and value that IP surveillance has to offer.



Hikvision UK
4 The Square,
Stockley Park, Uxbridge, UB11 1ET
Tel: 01628 902140
sales.uk@hikvision.com
support.uk@hikvision.com

DS-2CD2022WD-I

2MP MINI BULLET CAMERA WITH IR



- Full HD resolution 1080p (1920x1080@25ips)
- Lens options: 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CD2022WD-I(4MM)	0787060
DS-2CD2022WD-I(6MM)	0787070

DS-2CD2042WD-I

4MP MINI BULLET CAMERA WITH IR



- 4MP resolution (2688x1520@25ips, 1920x1080@25ips)
- Lens options: 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-XS

PART NO.	QUICK REF.
DS-2CD2042WD-I(4MM)	0782090
DS-2CD2042WD-I(6MM)	0787080

DS-2CD2122FWD-I

2MP INDOOR FIXED DOME CAMERA WITH IR



- Full HD resolution 1080p (1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- Indoor & IK10
- Built-in Micro SD / SDHC / SDXC card slot, up to 128GB
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1259ZJ DS-1272ZJ-110
DS-1272ZJ-110B DS-1280ZJ-DM18
DS-1276ZJ DS-1275ZJ DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD2122FWD-I(2.8MM)	0782100
DS-2CD2122FWD-I(4MM)	0789340
DS-2CD2122FWD-I(6MM)	0787090

DS-2CD2142FWD-I

4MP INDOOR FIXED DOME CAMERA WITH IR



- 4MP resolution (2688x1520@25ips, 1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- Indoor & IK10
- Built-in Micro SD / SDHC / SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1259ZJ DS-1272ZJ-110
DS-1272ZJ-110B DS-1280ZJ-DM18
DS-1276ZJ DS-1275ZJ DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD2142FWD-I(2.8MM)	0782110
DS-2CD2142FWD-I(4MM)	0782120
DS-2CD2142FWD-I(6MM)	0787100

DS-2CD2322WD-I

2MP WDR EXIR TURRET NETWORK CAMERA



- Full HD resolution 1080p (1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1273ZJ-130-TRL DS-1275ZJ
DS-1276ZJ DS-1280ZJ-M DS-1281ZJ-M

PART NO.	QUICK REF.
DS-2CD2322WD-I(2.8MM)	0782140
DS-2CD2322WD-I(4MM)	0782150
DS-2CD2322WD-I(6MM)	0787110

DS-2CD2342WD-I

4MP WDR EXIR TURRET NETWORK CAMERA



- 4MP resolution (2688x1520@25ips, 1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+ / H.264 / MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1273ZJ-130-TRL DS-1275ZJ
DS-1276ZJ DS-1280ZJ-M DS-1281ZJ-M

PART NO.	QUICK REF.
DS-2CD2342WD-I(2.8MM)	0782160
DS-2CD2342WD-I(4MM)	0782170
DS-2CD2342WD-I(6MM)	0783530

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-2CD2522FWD-I 2MP WDR MINIDOME NETWORK CAMERA



- Full HD resolution 1080p (1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 10m
- H.264+/H.264/MJPEG, dual-stream
- IP67 and IK08
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1272ZJ-120 DS-1272ZJ-120B
DS-1271ZJ-120 DS-1275ZJ DS-1276ZJ
DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD2522FWD-I(2.8MM)	0787120
DS-2CD2522FWD-I(4MM)	0787130
DS-2CD2522FWD-I(6MM)	0787140

DS-2CD2542FWD-I 4MP WDR MINIDOME NETWORK CAMERA



- 4MP resolution (2688x1520@25ips, 1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 10m
- H.264+/H.264/MJPEG, dual-stream
- IP67 and IK08
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1272ZJ-120 DS-1272ZJ-120B
DS-1271ZJ-120 DS-1275ZJ DS-1276ZJ
DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD2542FWD-I(2.8MM)	0787150
DS-2CD2542FWD-I(4MM)	0783540
DS-2CD2542FWD-I(6MM)	0783550

DS-2CD2622FWD-I(Z)(S) 2MP BULLET CAMERA WITH IR



- Full HD resolution 1080p (1920x1080@25ips)
- Lens: 2.8-12mm Varifocal
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- IP67
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Motorised lens (only -Z model)
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1260ZJ DS-1275ZJ DS-1280ZJ-S
DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD2622FWD-I(2.8-12MM)	0782190
DS-2CD2622FWD-I(Z)(2.8-12MM)	0787160
DS-2CD2622FWD-I(ZS)(2.8-12MM)	0787170

DS-2CD2642FWD-I(Z)(S) 4MP BULLET CAMERA WITH IR



- 4MP resolution (2688x1520@20ips, 1920x1080@25ips)
- Lens: 2.8-12mm Varifocal
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- IP67
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Motorised lens (only -Z model)
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1260ZJ DS-1275ZJ DS-1280ZJ-S
DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD2642FWD-I(2.8-12MM)	0782200
DS-2CD2642FWD-I(Z)(2.8-12MM)	0787180
DS-2CD2642FWD-I(ZS)(2.8-12MM)	0787190

DS-2CD2722FWD-I(Z)(S) 2MP WDR VARIFOCAL DOME NETWORK CAMERA



- Full HD resolution 1080p (1920x1080@25ips)
- Lens: 2.8-12mm Varifocal
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- IP67
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Motorised lens (only -Z model)
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1227ZJ DS-1273ZJ-135
DS-1273ZJ-135B DS-1280ZJ-DM21

PART NO.	QUICK REF.
DS-2CD2722FWD-I(2.8-12MM)	0782210
DS-2CD2722FWD-I(Z)(2.8-12MM)	0787200
DS-2CD2722FWD-I(ZS)(2.8-12MM)	0787210

DS-2CD2742FWD-I(Z)(S) 4MP WDR VARIFOCAL DOME NETWORK CAMERA



- 4MP resolution (2688x1520@20ips, 1920x1080@25ips)
- Lens: 2.8-12mm Varifocal
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- IP67
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- Motorised lens (only -Z model)
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1227ZJ DS-1273ZJ-135
DS-1273ZJ-135B DS-1280ZJ-DM21

PART NO.	QUICK REF.
DS-2CD2742FWD-I(2.8-12MM)	0782220
DS-2CD2742FWD-I(Z)(2.8-12MM)	0787220
DS-2CD2742FWD-I(ZS)(2.8-12MM)	0787230

DS-2CD2F22FWD-IW 2MP WDR MINI PT NETWORK CAMERA



- Full HD resolution 1080p (1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 10m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- Support Wi-Fi
- Pan: -90°~90°, Tilt: 0°~75°
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1294ZJ

PART NO.	QUICK REF.
DS-2CD2F22FWD-IW(2.8MM)	0787240
DS-2CD2F22FWD-IW(4MM)	0787250
DS-2CD2F22FWD-IW(6MM)	0787260

DS-2CD2F42FWD-IW 4MP WDR MINI PT NETWORK CAMERA



- 4MP resolution (2688x1520@20ips, 1920x1080@25ips)
- Lens options: 2.8mm, 4mm, 6mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 10m
- H.264+/H.264/MJPEG, dual-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- Support Wi-Fi
- Pan: -90°~90°, Tilt: 0°~75°
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1294ZJ

PART NO.	QUICK REF.
DS-2CD2F42FWD-IW(2.8MM)	0787270
DS-2CD2F42FWD-IW(4MM)	0787280
DS-2CD2F42FWD-IW(6MM)	0787290

DS-2CD2T22WD-I3/I5/I8 2MP EXIR NETWORK BULLET CAMERA



- Full HD resolution 1080p (1920x1080@25ips)
- Lens: -I3: 4.6mm; -I5: 4, 6, 12mm; -I8: 6, 12, 16mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- Up to 30/50/80m IR range
- H.264+/H.264/MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD2T22WD-I3(4MM)	0787300
DS-2CD2T22WD-I3(6MM)	0787310
DS-2CD2T22WD-I5(4MM)	0782230
DS-2CD2T22WD-I5(6MM)	0787320
DS-2CD2T22WD-I5(12MM)	0787330
DS-2CD2T22WD-I8(6MM)	0787340
DS-2CD2T22WD-I8(12MM)	0788560
DS-2CD2T22WD-I8(16MM)	0788570

DS-2CD2T42WD-I3/I5/I8 4MP EXIR NETWORK BULLET CAMERA



- 4MP resolution (2688x1520@20ips, 1920x1080@25ips)
- Lens: -I3: 4.6mm; -I5: 4, 6, 12mm; -I8: 6, 12, 16mm
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- Up to 30/50/80m IR range
- H.264+/H.264/MJPEG, dual-stream
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD2T42WD-I3(4MM)	0787350
DS-2CD2T42WD-I3(6MM)	0787360
DS-2CD2T42WD-I5(4MM)	0782240
DS-2CD2T42WD-I5(6MM)	0787370
DS-2CD2T42WD-I5(12MM)	0787380
DS-2CD2T42WD-I8(6MM)	0787390
DS-2CD2T42WD-I8(12MM)	0787400
DS-2CD2T42WD-I8(16MM)	0788580

DS-2CD2942F-I 4MP COMPACT FISHEYE CAMERA



NEW

- 4MP resolution (2560x1440@12.5ips, 1920x1080@25ips)
- Lens options: 1.6mm
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 8m
- H.264/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- Power 12VDC or 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1294ZJ DS-1281ZJ-DM27 DS-1297ZJ DS-1203ZJ

PART NO.	QUICK REF.
DS-2CD2942F-IS(1.6MM)	0783580

DS-2CD4B26FWD-I2S 2MP ULTRA-LOW LIGHT SMART BULLET CAMERA



NEW

DARKFIGHTER

- Full HD resolution 1080p (1920x1080@25ips)
- Lens: 2.8~12mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, Intrusion detection
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4B26FWD-I2S(2.8-12mm)	0787420

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-2CD4D26FWD-IZS 2MP ULTRA-LOW LIGHT SMART DOME CAMERA



NEW

DARKFIGHTER

- Full HD resolution 1080p (1920x1080@25ips)
- Lens: 2.8-12mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, intrusion detection
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP66
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1271ZJ-DM30 DS-1271ZJ-DM32
DS-1273ZJ-DM30-B DS-1273ZJ-DM32

PART NO.	QUICK REF.
DS-2CD4D26FWD-IZS(2.8-12MM)	0787440

DS-2CD4126FWD-IZ 2MP ULTRA-LOW LIGHT INDOOR DOME CAMERA



NEW

DARKFIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1273ZJ-130B DS-1273ZJ-130
DS-1271ZJ-130 DS-1227ZJ

PART NO.	QUICK REF.
DS-2CD4126FWD-IZ(2.8-12MM)	0783630

DS-2CD4526FWD-IZ(H)(S) 2MP ULTRA-LOW LIGHT OUTDOOR DOME CAMERA



NEW

DARKFIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 40m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IP66 & IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-DM26 DS-1281ZJ-DM26
DS-1273ZJ-DM26 DS-1273ZJ-DM26-B DS-1271ZJ-DM26
6P-FE1 DS-1250ZJ DS-1275ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4526FWD-IZ(2.8-12MM)	0783640
DS-2CD4526FWD-IZ(H)(2.8-12MM)	0788590

DS-2CD4626FWD-IZ(H)(S) 2MP ULTRA-LOW LIGHT VANDAL-PROOF BULLET CAMERA



DARKFIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 70m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting, ANPR function
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP66 & IK10
- Power 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ-4626

PART NO.	QUICK REF.
DS-2CD4626FWD-IZ(2.8-12MM)	0783660
DS-2CD4626FWD-IZHS(2.8-12MM)	0787450

DS-2CD4A26FWD-IZ(H)(S) 2MP ULTRA-LOW LIGHT OUTDOOR BULLET CAMERA



DARKFIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal, 8-32mm Varifocal
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 50m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting, ANPR function
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ
DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4A26FWD-IZ(2.8-12MM)	0787460
DS-2CD4A26FWD-IZHS(2.8-12MM)	0783680
DS-2CD4A26FWD-IZ(8-32MM)	0787470
DS-2CD4A26FWD-IZHS(8-32MM)	0787480

DS-2CD4125FWD-IZ 2MP ULTRA WDR INDOOR DOME CAMERA



LIGHTFIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal
- 0.005 lux @ (F1.2, AGC ON), 0.007 lux @ (F1.4, AGC ON), 0 lux with IR
- 140dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1273ZJ-130B DS-1273ZJ-130
DS-1271ZJ-130 DS-1227ZJ

PART NO.	QUICK REF.
DS-2CD4125FWD-IZ(2.8-12MM)	0787490

DS-2CD4525FWD-IZ(H) 2MP ULTRA WDR OUTDOOR DOME CAMERA



LIGHT FIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal, 8-32mm Varifocal
- 0.005 lux @ (F1.2, AGC ON), 0.007 lux @ (F1.4, AGC ON), 0 lux with IR
- 140dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR Distance up to 40m (2.8-12mm)/50m (8-32mm)
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IP66 & IK10
- Power 12VDC/24VAC/PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-DM26 DS-1281ZJ-DM26
DS-1273ZJ-DM26 DS-1273ZJ-DM26-B DS-1271ZJ-DM26

PART NO.	QUICK REF.
DS-2CD4525FWD-IZ(2.8-12MM)	0787500
DS-2CD4525FWD-IZH(2.8-12MM)	0787510
DS-2CD4525FWD-IZ(8-32MM)	0787520
DS-2CD4525FWD-IZH(8-32MM)	0787530

DS-2CD4A25FWD-IZ(H)(S) 2MP ULTRA WDR OUTDOOR BULLET CAMERA



LIGHT FIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal, 8-32mm Varifocal
- 0.005 lux @ (F1.2, AGC ON), 0.007 lux @ (F1.4, AGC ON), 0 lux with IR
- 140dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR Distance up to 50m (2.8-12mm)/100m (8-32mm)
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting, anpr function
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4A25FWD-IZ(2.8-12MM)	0787540
DS-2CD4A25FWD-IZHS(2.8-12MM)	0787550
DS-2CD4A25FWD-IZ(8-32MM)	0787560
DS-2CD4A25FWD-IZHS(8-32MM)	0787570

DS-2CD4625FWD-IZ(H)(S) 2MP ULTRA WDR VANDAL-PROOF BULLET CAMERA



LIGHT FIGHTER

- Full HD resolution 1080p (1920x1080@50ips)
- Lens: 2.8-12mm Varifocal, 8-32mm Varifocal
- 0.005 lux @ (F1.2, AGC ON), 0.007 lux @ (F1.4, AGC ON), 0 lux with IR
- 140dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR Distance up to 50m (2.8-12mm)/120m (8-32mm)
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting, ANPR function
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP66 & IK10
- Power 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ-4626

PART NO.	QUICK REF.
DS-2CD4625FWD-IZ(2.8-12MM)	0787580
DS-2CD4625FWD-IZHS(2.8-12MM)	0787590
DS-2CD4625FWD-IZ(8-32MM)	0787600
DS-2CD4625FWD-IZHS(8-32MM)	0787610

DS-2CD4165F-IZ 6MP SMART IP INDOOR DOME CAMERA



- 6MP resolution (3072x2048@20ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1273ZJ-130B DS-1273ZJ-130
DS-1271ZJ-130 DS-1227ZJ

PART NO.	QUICK REF.
DS-2CD4165F-IZ(2.8-12MM)	0787620

DS-2CD4565F-IZ(H) 6MP SMART IP OUTDOOR DOME CAMERA



- 6MP resolution (3072x2048@20ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 40m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-DM26 DS-1281ZJ-DM26
DS-1273ZJ-DM26 DS-1273ZJ-DM26-B
DS-1271ZJ-DM26 DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD4565F-IZ(2.8-12MM)	0787630
DS-2CD4565F-IZH(2.8-12MM)	0787640

DS-2CD4A65F-IZ(H)(S) 6MP SMART IP OUTDOOR BULLET CAMERA



- 6MP resolution (3072x2048@20ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 50m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MPEG4/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4A65F-IZ(2.8-12MM)	0787650
DS-2CD4A65F-IZHS(2.8-12MM)	0787660

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com



The Best Way to Get Panoramic Views and Incredible Detail in One Camera!

Hikvision PanoVu Series Panoramic Cameras

Pan out to get the whole scenario in one frame. Then zoom in to see a single face in the crowd. And get the most advanced surveillance technology at the same time.

Sensors inside the PanoVu Series Cameras stitch together multiple video streams into one panoramic shot much more efficiently than software. Bring entire stadiums, plazas, airports, and open areas of all kinds into 180- and 360-degree panoramic view. Then, from the panoramic view, swiftly zoom in on a target for incredibly close-up detail with 36X optical zoom. With PanoVu, you get the most powerful "Vu" in security surveillance.



**DESIGN
AWARD
2016**



Hikvision UK
4 The Square,
Stockley Park, Uxbridge, UB11 1ET
Tel: 01628 902140
sales.uk@hikvision.com
support.uk@hikvision.com

DS-2CD4665F-IZ(H)(S) 6MP SMART IP VANDAL-PROOF BULLET CAMERA



- 6MP resolution (3072×2048@20ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 50m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP66 & IK10
- Power 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ-4626

PART NO.	QUICK REF.
DS-2CD4665F-IZ(2.8-12MM)	0787670
DS-2CD4665F-IZHS(2.8-12MM)	0787680

DS-2CD4185F-IZ 8MP SMART INDOOR DOME CAMERA



- 8MP resolution (4096×2160@22ips, 3840×2160@25ips, 1920×1080@25ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1271ZJ-130 DS-1273ZJ-130
DS-1273ZJ-130B DS-1227ZJ DS-1275ZJ
DS-1276ZJ DS-1280ZJ-DM21 DS-1281ZJ-DM23
DS-1253ZJ-L DS-1250ZJ

PART NO.	QUICK REF.
DS-2CD4185F-IZ(2.8-12MM)	0788600

DS-2CD4585F-IZ 8MP SMART OUTDOOR DOME CAMERA



- 8MP resolution (4096×2160@22ips, 3840×2160@25ips, 1920×1080@25ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 40m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IP66 & IK10
- Power 12VDC or 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-DM26 DS-1281ZJ-DM26
DS-1273ZJ-DM26 DS-1273ZJ-DM26-B
DS-1271ZJ-DM26 GP-FE1 DS-1250ZJ DS-1275ZJ
DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4585F-IZ(2.8-12MM)	0789510

DS-2CD4685F-IZ(H)(S) 8MP SMART CAMERA



- 8MP resolution (4096×2160@22ips, 3840×2160@25ips, 1920×1080@25ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 70m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP66 & IK10
- Power 24VAC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ-4626

PART NO.	QUICK REF.
DS-2CD4685F-IZ(2.8-12MM)	0787690
DS-2CD4685F-IZHS(2.8-12MM)	0787700

DS-2CD4A85F-IZ(H)(S) 8MP SMART BULLET CAMERA



- 8MP resolution (4096×2160@22ips, 3840×2160@25ips, 1920×1080@25ips)
- Lens: 2.8-12mm Varifocal
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 50m
- Line crossing detection, intrusion detection, region entrance, region exiting, unattended baggage, object removal, face detection, object counting
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out (only -S model)
- IP67
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1275ZJ DS-1280ZJ-S DS-1260ZJ
DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD4A85F-IZ(2.8-12MM)	0787710
DS-2CD4A85F-IZHS(2.8-12MM)	0787720

DS-2CD6362F-IVS 6MP FISHEYE CAMERA



- 6MP resolution (3072×2048@25ips)
- Lens: 1.27mm
- Colour: 0.05 lux @(F1.2, AGC ON), B/W: 0.3 lux @(F2.0, AGC ON), 0 lux with IR
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 15m
- Heat Mapping
- H.264/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IP66
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1271ZJ-DM25 DS-1273ZJ-DM25
DS-1280ZJ-DM25 DS-1281ZJ-DM25 DS-1283ZJ
DS-1275ZJ DS-1276ZJ

PART NO.	QUICK REF.
DS-2CD6362F-IVS(1.27MM)	0787730

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-2CD63C2F-IVS 12MP FISHEYE CAMERA



NEW

- 12MP resolution (4000×3072@25ips)
- Lens options: 2mm
- Colour: 0.01 lux @ (F1.2, AGC ON), B/W: 0.04 lux @ (F2.4, AGC ON), 0 lux with IR
- Digital Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 15m
- Heat Mapping
- H.264/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IP66 & IK10
- Power 12VDC or PoE (Power over Ethernet)

Bracket(s): DS-1280ZJ-DM25 DS-1281ZJ-DM25
DS-1273ZJ-DM25 DS-1271ZJ-DM25 DS-2CD1283ZJ

PART NO.	QUICK REF.
DS-2CD63C2F-IVS(2MM)	0787740

DS-2CD6412FWD-20 1.3MP COVERT NETWORK CAMERA



- 1.3MP resolution (1280×960@25ips)
- Lens options: -L10/L20/10/20: 2.8/3.7mm@ F2.3
- Colour: 0.037 lux @ (F2.3, AGC ON), B/W: 0.0037 lux @ (F2.3, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- HLC, Defog and EIS
- Length of lens cable: 2m/8m
- H.264/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- Power 12VDC or PoE (Power over Ethernet)

PART NO.	QUICK REF.
DS-2CD6412FWD-20/2M	0783710
DS-2CD6412FWD-20/8M	0787750

DS-2CD6986F-(H) 8MP PANORAMIC DOME CAMERA



NEW

- 8MP Ultra HD resolution (4096×1800@25ips)
- Lens: 4×5mm
- Colour: 0.002 lux @ (F1.2, AGC ON), B/W: 0.0002 lux @ (F1.2, AGC ON), 0 lux with IR
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- IR illumination up to 30m
- H.264+/H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 1-ch alarm in/out
- IK10
- Power 12VDC or PoE (Power over Ethernet)
- "H": Heater

Bracket(s): DS-1271ZJ-DM30 DS-1273ZJ-DM30
DS-1273ZJ-DM30-B

PART NO.	QUICK REF.
DS-2CD6986F(5MM)	0785510
DS-2CD6986F-H(5MM)	0789060

DS-2DP1636Z-D PANORAMIC+PTZ CAMERA



NEW

- 2×4096×1800@25ips
- Lens: Panoramic camera 8×5mm; tracking PTZ camera: 5.7-205.2mm, 36×
- Panoramic camera: Colour: 0.005 lux @ (F1.8, AGC ON), B/W: 0.0005 lux @ (F1.8, AGC ON)
- Tracking PTZ camera: Colour: 0.002 lux @ (F1.8, AGC ON), B/W: 0.0002 lux @ (F1.8, AGC ON)
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), High Light Compensation (HLC)
- H.264/MJPEG, triple-stream
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 7/2 alarm in/out
- IP66
- Power 36VDC

Bracket(s): DS-1603ZJ DS-1668ZJ
DS-1668ZJ(20)

PART NO.	QUICK REF.
DS-2DP1636Z-D(5MM)	0788610

DS-2DP0818Z-D 180° PANORAMA+PTZ CAMERA



NEW

- 8MP Ultra HD resolution (4096×1800@25ips)
- Lens: Panoramic camera 4×5mm; tracking PTZ camera: 5.7-205.2mm, 36×
- Panoramic camera: Colour: 0.005 lux @ (F2.2, AGC ON), B/W: 0.0005 lux @ (F2.2, AGC ON)
- Tracking PTZ camera: Colour: 0.002 lux @ (F1.5, AGC ON), B/W: 0.0002 lux @ (F1.5, AGC ON)
- 120dB Wide Dynamic Range, 3D Digital Noise Reduction (DNR), High Light Compensation (HLC)
- H.264 (Baseline, Main, High Profile)/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 1-ch audio in/out, 7/2 alarm in/out
- IP66
- Power 36VDC

Bracket(s): DS-1603ZJ DS-1668ZJ
DS-1668ZJ(20)

PART NO.	QUICK REF.
DS-2DP0818Z-D(5MM)	0788620

DS-2DP1636-D PANORAMIC CAMERA



NEW

- Resolution: 2×2400×3840@25ips
- Lens: 8×4mm
- Colour: 0.004 lux @ (F1.8, AGC ON), B/W: 0.0004 Lux @ (F1.8, AGC ON)
- 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264 (Baseline, Main, High Profile)/MJPEG
- Built-in Micro SD/SDHC/SDXC card slot, up to 128GB
- 7 alarm inputs (0-5VDC), 2 alarm output, Support alarm linkage
- IP66
- Power 36VDC

Bracket(s): DS-1603ZJ DS-1668ZJ
DS-1668ZJ(20)

PART NO.	QUICK REF.
DS-2DP1636-D(4MM)	0788630

HIKVISION®



As voted for by security
and fire systems installers

Ultra-low Light Performance

Captures crystal-clear colour images down to as low as 0.002 lux and B/W to 0.0002 lux.

Superior Zoom

Features up to 36x optical zoom to magnify tiny details for remote objects.

Full Smart Feature-set

Supports Smart functions including intrusion detection, line crossing detection, as well as Smart Tracking to improve operational convenience.

Smart Codec

Hikvision H.264+ Smart Codec further powers the system by reducing bandwidth and storage requirements by up to 50%.



WE WON! HIKVISION ULTRA-LOW LIGHT
DARKFIGHTER PTZ CAMERAS

2016 Winner of PSI Premier Awards in the 'CCTV Product of the Year' Category.



Hikvision UK
4 The Square,
Stockley Park, Uxbridge, UB11 1ET
Tel: 01628 902140
sales.uk@hikvision.com
support.uk@hikvision.com

www.hikvision.com

DS-2DE4220-AE/AE3

2MP PTZ (20X) CAMERA (OUTDOOR READY)



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4.7-94mm
- 20× Optical zoom, 16× Digital zoom
- Digital Wide Dynamic Range (DWDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG, dual-stream
- IP66 standard (outdoor dome)
- Built-in micro SD card slot, up to 128GB, support edge recording
- Power 24VAC/PoE+ (802.3at), Max. 18W
- AE: outdoor, AE3: indoor

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ
DS-1602ZJ-pole DS-1602ZJ-corner
DS-1602ZJ-box DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2DE4220-AE	0783730
DS-2DE4220-AE3	0783740

DS-2DE4220IW-DE

2MP 20X NETWORK IR PTZ DOME CAMERA



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4.7-94mm
- 20× Optical zoom, 16× Digital zoom
- IR illumination up to 100m
- Digital Wide Dynamic Range (DWDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG, dual-stream
- Outdoor ready IP66
- Built-in micro SD card slot, up to 128GB, support edge recording
- Power 12VDC & PoE (802.3at, class4), Max. 20W

Bracket(s): DS-1602ZJ DS-1602ZJ-corner
DS-1602ZJ-pole DS-1602ZJ-box DS-1619ZJ

PART NO.	QUICK REF.
DS-2DE4220IW-DE	0787760

DS-2DE5220IW-AE

2MP 20X NETWORK IR PTZ DOME CAMERA



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4.7-94mm
- 20× Optical zoom, 16× Digital zoom
- IR illumination up to 150m
- Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG, dual-stream
- IP66
- Built-in micro SD card slot, up to 128GB, support edge recording
- Power High-PoE & 24VAC, Max. 40W

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ
DS-1602ZJ-pole DS-1602ZJ-corner
DS-1602ZJ-box DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2DE5220IW-AE	0787770

DS-2DE5220W-AE/AE3

2MP PTZ (20X) CAMERA (OUTDOOR READY)



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4.7-94mm
- 20× Optical zoom, 16× Digital zoom
- Digital Wide Dynamic Range (DWDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG, dual-stream
- IP66 standard (outdoor dome)
- Built-in micro SD card slot, up to 128GB, support edge recording
- Power 24VAC/PoE+ (802.3at), Max. 18W
- AE: outdoor, AE3: indoor

Bracket(s): DS-1602ZJ DS-1602ZJ-corner
DS-1602ZJ-pole DS-1602ZJ-box

PART NO.	QUICK REF.
DS-2DE5220W-AE	0787780
DS-2DE5220W-AE3	0787790

DS-2DE7230IW-AE

2MP 30X NETWORK IR PTZ DOME CAMERA



- Full HD resolution 1080p (1920×1080@25ips)
- Lens: 4.7-129mm
- 30× Optical zoom, 16× Digital zoom
- IR illumination up to 150m
- Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG, dual-stream
- IP66
- Built-in micro SD card slot, up to 128GB, support edge recording
- Power High-PoE & 24VAC, Max. 40W

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ
DS-1602ZJ-pole DS-1602ZJ-corner
DS-1602ZJ-box DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2DE7230IW-AE	0787800

DS-2DF8223I-AEL(W)

2MP ULTRA LOW LIGHT PTZ CAMERA



- HD resolution 1080p (1920×1080@25ips)
- Lens: 5.9-135.7mm
- 23× Optical zoom, 16× Digital zoom
- Up to 200m IR distance
- Digital Wide Dynamic Range (DWDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG/MPEG4, triple-stream
- Alarm in/out: 7/2
- Built-in micro SD card slot, up to 128GB, support edge recording
- Face detection, intrusion detection, line crossing detection, audio exception detection, region entrance detection, region exiting detection
- Audio in/out: 1/1
- W: wiper

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ
DS-1602ZJ-pole DS-1602ZJ-corner
DS-1602ZJ-box DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2DF8223I-AEL	0782470
DS-2DF8223I-AELW	0782480

DS-2DF8236I-AEL(W) 2MP ULTRA-LOW LIGHT PTZ CAMERA



- HD resolution 1080p (1920×1080@25ips)
- Lens: 5.7-205.2mm
- 36× Optical zoom, 16× Digital zoom
- Up to 200m IR distance
- Digital Wide Dynamic Range (DWDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG/MPEG4, triple-stream
- Alarm in/out: 7/2
- Built-in micro SD card slot, up to 128GB, support edge recording
- Face detection, intrusion detection, line crossing detection, audio exception detection, region entrance detection, region exiting detection
- Audio in/out: 1/1
- W: wiper

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ
DS-1602ZJ-pole DS-1602ZJ-corner
DS-1602ZJ-box DS-1602ZJ-BOX-POLE
DS-1602ZJ-BOX-CORNER DS-1619ZJ

PART NO.	QUICK REF.
DS-2DF8236I-AEL	0787810
DS-2DF8236I-AELW	0787820

DS-2DF8836IV-AELW 8MP ULTRA HD PTZ CAMERA



- 8MP resolution (4096×2160@25ips)
- Lens: 6.2-202mm
- 36× Optical zoom, 16× Digital zoom
- Up to 200m IR distance
- Wide Dynamic Range (WDR), 3D Digital Noise Reduction (DNR), Back Light Compensation (BLC)
- H.264/MJPEG/MPEG4, triple-stream
- Alarm in/out: 7/2
- Built-in micro SD card slot, up to 128GB, support edge recording
- Face detection, intrusion detection, line crossing detection, audio exception detection, region entrance detection, region exiting detection
- Audio in/out: 1/1
- W: wiper

Bracket(s): DS-1661ZJ DS-1662ZJ DS-1663ZJ
DS-1618ZJ DS-1660ZJ DS-1602ZJ DS-1602ZJ-pole
DS-1602ZJ-corner DS-1602ZJ-box
DS-1602ZJ-BOX-POLE DS-1602ZJ-BOX-CORNER
DS-1619ZJ

PART NO.	QUICK REF.
DS-2DF8836IV-AELW	0789110

NVR Comparison Chart

PRODUCT		DS-7677NI-E2/E4(/XP)	DS-767700NI-K2/K4(/XP)	DS-767700NI-I2/I4(/XP)	DS-9600NI-I8/I16	DS-9600NI-F16/F24(/H)
IP CHANNEL NO.		8-ch/16-ch/32-ch	8-ch/16-ch/32-ch	8-ch/16-ch/32-ch	16-ch/32-ch	128-ch/256-ch
RECORDING RESOLUTION		Up to 6MP	Up to 4K (8MP)	Up to 4K (8MP) and 12MP	Up to 4K (8MP) and 12MP	Up to 4K (8MP)
INCOMING BANDWIDTH		80/160/160Mbps	80/160/256Mbps	80/160/256Mbps	320/320 Mbps (200Mbps when enabling Raid)	128-ch: 400Mbps, 256-ch: 640Mbps (400Mbps if soft raid is enabled)
OUTGOING BANDWIDTH		80/80/80Mbps	160/160/160Mbps	256/256/256Mbps	256/256Mbps (200Mbps when enabling Raid)	400Mbps
DECODING CAPABILITY		12-ch @720p, 6-ch @1080p	2-ch @4K, 8-ch @1080p	8-channel: 2-ch @4K, 8-ch @1080p 16/32-channel: 4-ch @4K, 16-ch @1080p	32/64-channel: 4-ch @4K, 16-ch @1080p	8-ch@1080p I/H models: 44-ch@1080p
VIDEO OUTPUT	HDMI/VGA	1VGA, 1HDMI (simultaneous output; HDMI supports 1080p@60Hz output)	1VGA, 1HDMI (non-simultaneous output; HDMI supports 4K @30Hz output)	1VGA, 1HDMI (independent output; HDMI supports 4K@60Hz output)	2VGA, 2HDMI (independent output; HDMI 1 supports 4K@60Hz output)	1VGA, 2HDMI (simultaneous output; HDMI supports 1080p@60Hz output)
	BNC	N/A	N/A	1-ch Optional	1-ch Optional	N/A
DECODING STANDARD		H.264/H.264+	H.264/H.264+/H.265	H.264/H.264+/H.265	H.264/H.264+/H.265	H.264/H.264+
eSATA		1 Optional (only for DS-7700NI-E series)	1 Optional (only for DS-7700NI series)	1 Optional (only for DS-7700NI series)	Yes	N/A
ALARM I/O (DEFAULT)		4/1(DS-7600NI-E2)	4/1(DS-7600NI-K2)	DS-7600 series: 4/1 DS-7700 series: 16/4	16/4	16 in, 8 out
HARD DISK		DS-7600 series: Up to 2x HDDs, DS-7600 series: Up to 4x HDDs	DS-7600 series: Up to 2x HDDs, DS-7600 series: Up to 4x HDDs	DS-7600 series: Up to 2x HDDs, DS-7600 series: Up to 4x HDDs	I8: 8x HDDs I16: 16x HDDs	16/24SATA+1mini SAS (optional)
RAID		N/A	N/A	N/A	Yes	Yes

DS-7604NI-E1/4P(/A) 4 CHANNEL NVR 1U CASE



- Up to 4 channel IP video
- Up to 5MP resolution recording
- 1 SATA interface
- Incoming bandwidth: 25Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 4 port PoE+ switch (Max. 50W)
- Power Supply: 12VDC ≤ 10W
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

DS-7608NI-E2/8P(/A) 8 CHANNEL NVR 1U 19" CASE



- Up to 8 channel IP video
- Up to 5MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 50Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

DS-7616NI-E2/8P(/A) 16 CHANNEL NVR 1U 19" CASE



- Up to 16 channel IP video
- Up to 5MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 100Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7604NI-E1/4P	0782560
DS-7604NI-E1/4P/A	0782570

PART NO.	QUICK REF.
DS-7608NI-E2/8P	0782580
DS-7608NI-E2/8P/A	0782590

PART NO.	QUICK REF.
DS-7616NI-E2/8P	0787850
DS-7616NI-E2/8P/A	0787860

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-7708NI-E4/8P
8 CHANNEL NVR 1.5U 19" CASE



- Up to 8 channel IP video
- Up to 6MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 80Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 8 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4 (optionally can be expanded to 16/8)
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7708NI-E4/8P	0787870

DS-7716NI-E4/16P
16 CHANNEL NVR 1.5U 19" CASE



- Up to 16 channel IP video
- Up to 6MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 160Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4 (optionally can be expanded to 16/8)
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7716NI-E4/16P	0782610

DS-7732NI-E4/16P
32 CHANNEL NVR 1.5U 19" CASE



- Up to 32 channel IP video
- Up to 6MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 160Mbps
Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4 (optionally can be expanded to 16/8)
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7732NI-E4/16P	0787880

DS-7608NI-I2/8P
8 CHANNEL 4K NVR 1U 19" CASE



- Up to 8 channel IP video
- Up to 12MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 80Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840x2160) resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7608NI-I2/8P	0787890

DS-7616NI-I2/16P
16 CHANNEL 4K NVR 1U 19" CASE



- Up to 16 channel IP video
- Up to 12MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 160Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840x2160) resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7616NI-I2/16P	0782600

DS-7632NI-I2/16P
32 CHANNEL 4K NVR 1U 19" CASE



- Up to 32 channel IP video
- Up to 12MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 256Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 4K (3840x2160) resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7632NI-I2/16P	0787920

DS-7708NI-I4/8P

8 CHANNEL 4K NVR 1.5U 19" CASE



- Up to 8 channel IP video
- Up to 12MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 80Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- HDMI & VGA video output at up to 4K (3840x2160) resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.

DS-7708NI-I4/8P

QUICK REF.

0787940

DS-7716NI-I4/16P

16 CHANNEL 4K NVR 1.5U 19" CASE



- Up to 16 channel IP video
- Up to 12MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 160Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- HDMI & VGA video output at up to 4K (3840x2160) resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.

DS-7716NI-I4/16P

QUICK REF.

0782620

DS-7732NI-I4/16P

32 CHANNEL 4K NVR 1.5U 19" CASE



- Up to 32 channel IP video
- Up to 1MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 256Mbps
Outgoing bandwidth: 256Mbps
- Video Compression H.265/H.264/MPEG4
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- HDMI & VGA video output at up to 4K (3840x2160) resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.

DS-7732NI-I4/16P

QUICK REF.

0787950

DS-9632NI-I8

32 CHANNEL 4K NVR 2U 19" CASE



- Up to 32 channel IP video
- Up to 12MP resolution recording
- 8 SATA interfaces
- Incoming bandwidth: 320Mbps or 200Mbps (when RAID is enabled),
Outgoing bandwidth: 256Mbps or 200Mbps (when RAID is enabled)
- Video Compression H.265/H.264/MPEG4
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 2-ch HDMI, 2-ch VGA, HMDi1 at up to 4K (3840x2160) resolution
- Support HDD hot swap with RAID 0, 1, 5, 6, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.

DS-9632NI-I8

QUICK REF.

0783810

DS-9664NI-I8

64 CHANNEL 4K NVR 2U 19" CASE



- Up to 64 channel IP video
- Up to 12MP resolution recording
- 8 SATA interfaces
- Incoming bandwidth: 320Mbps or 200Mbps (when RAID is enabled),
Outgoing bandwidth: 256Mbps or 200Mbps (when RAID is enabled)
- Video Compression H.265/H.264/MPEG4
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 2-ch HDMI, 2-ch VGA, HMDi1 at up to 4K (3840x2160) resolution
- Support HDD hot swap with RAID 0, 1, 5, 6, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.

DS-9664NI-I8

QUICK REF.

0783820

DS-96128NI-F16/H

128 CHANNEL SUPER NVR 3U 19" CASE



- Up to 128 channel IP video
- Up to 8MP resolution recording
- 16 SATA interfaces
- Incoming bandwidth: 400Mbps,
Outgoing bandwidth: 400Mbps
- Video Compression H.264/MPEG4
- 4 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 14-ch HDMI, 1-ch VGA, up to 1080p (1920x1080) resolution
- Support HDD hot swap with RAID 0, 1, 5, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- 2x USB 2.0 & 2x USB 3.0
- Third-party network cameras supported

PART NO.

DS-96128NI-F16/H

QUICK REF.

0787960

DS-96256NI-F16/H

256 CHANNEL SUPER NVR 3U 19" CASE



- Up to 256 channel IP video
- Up to 8MP resolution recording
- 16 SATA interfaces
- Incoming bandwidth: 640Mbps or 400Mbps (when RAID is enabled), Outgoing bandwidth: 400Mbps
- Video Compression H.264/MPEG4
- 4 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 14-ch HDMI, 1-ch VGA, up to 1080p (1920x1080) resolution
- Support HDD hot swap with RAID 0, 1, 5, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- 2× USB 2.0 & 2× USB 3.0
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-96256NI-F16/H	0787970

DS-96128NI-F24/H

128 CHANNEL SUPER NVR 3U 19" CASE



- Up to 128 channel IP video
- Up to 8MP resolution recording
- 24 SATA interfaces
- Incoming bandwidth: 400Mbps, Outgoing bandwidth: 400Mbps
- Video Compression H.264/MPEG4
- 4 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 14-ch HDMI, 1-ch VGA, up to 1080p (1920x1080) resolution
- Support HDD hot swap with RAID 0, 1, 5, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- 1× USB 2.0 & 2× USB 3.0
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-96128NI-F24/H	0787980

DS-96256NI-F24/H

256 CHANNEL SUPER NVR 3U 19" CASE




- Up to 256 channel IP video
- Up to 8MP resolution recording
- 24 SATA interfaces
- Incoming bandwidth: 640Mbps or 400Mbps (when RAID is enabled), Outgoing bandwidth: 400Mbps
- Video Compression H.264/MPEG4
- 4 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- 14-ch HDMI, 1-ch VGA, up to 1080p (1920x1080) resolution
- Support HDD hot swap with RAID 0, 1, 5, 10 storage scheme configurable
- Power Supply: 100 to 240VAC, 50 to 60Hz
- 1× USB 2.0 & 2× USB 3.0
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-96256NI-F24/H	0787990

DS-7604NI-K1/4P

4 CHANNEL COST-EFFECTIVE 4K NVR 1U CASE



- Up to 4 channel IP video
- Up to 8MP resolution recording
- 1 SATA interface
- Incoming bandwidth: 40Mbps Outgoing bandwidth: 80Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 4 port PoE+ switch (Max. 50W)
- Power Supply: 48VDC ≤ 10W
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7604NI-K1/4P	0788000

DS-7608NI-K2/8P

8 CHANNEL COST-EFFECTIVE 4K NVR 1U CASE



- Up to 8 channel IP video
- Up to 8MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 80Mbps Outgoing bandwidth: 160Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- HDMI and VGA output at up to 1920×1080p resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7608NI-K2/8P	0788020

DS-7616NI-K2/16P

16 CHANNEL COST-EFFECTIVE 4K NVR 1U CASE



- Up to 16 channel IP video
- Up to 8MP resolution recording
- 2 SATA interface
- Incoming bandwidth: 160Mbps Outgoing bandwidth: 160Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7616NI-K2/16P	0788040

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-7632NI-K2/16P

32 CHANNEL COST-EFFECTIVE 4K NVR 1U CASE



- Up to 32 channel IP video
- Up to 8MP resolution recording
- 2 SATA interfaces
- Incoming bandwidth: 256Mbps
Outgoing bandwidth: 160Mbps
- Video Compression H.264, MPEG4
- 1RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- /A: Alarm 4 input/1 output
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7632NI-K2/16P	0788060

DS-7708NI-K4/8P

8 CHANNEL COST-EFFECTIVE 4K NVR 1.5U 19" CASE



- Up to 8 channel IP video
- Up to 8MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 80Mbps
Outgoing bandwidth: 160Mbps
- Video Compression H.265/H.264/MPEG4
- 1 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 8 port PoE+ switch (Max. 120W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7708NI-K4/8P	0788080

DS-7716NI-K4/16P

16 CHANNEL COST-EFFECTIVE 4K NVR 1.5U 19" CASE



- Up to 16 channel IP video
- Up to 8MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 160Mbps
Outgoing bandwidth: 160Mbps
- Video Compression H.265/H.264/MPEG4
- 1 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7716NI-K4/16P	0788090

DS-7732NI-K4/16P

32 CHANNEL COST-EFFECTIVE 4K NVR 1.5U 19" CASE



- Up to 32 channel IP video
- Up to 8MP resolution recording
- 4 SATA interfaces
- Incoming bandwidth: 256Mbps
Outgoing bandwidth: 160Mbps
- Video Compression H.265/H.264/MPEG4
- 1 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- VGA output at up to 1920×1080p resolution, HDMI output at up to 3840×2160 resolution
- Built-in 16 port PoE+ switch (Max. 200W)
- Power Supply: 100 to 240VAC, 50 to 60Hz
- Alarm in/out 16/4
- Third-party network cameras supported

PART NO.	QUICK REF.
DS-7732NI-K4/16P	0788100



A SIMPLE iVMS STATION WITH ENORMOUS POTENTIAL

Delivering simplified and smart CCTV solutions for the SMB market

Hikvision Blazer Express combines a VMS software and hardware solution in one compact unit. It was designed specifically to enhance small-to medium-sized chain-store networks, enabling operators to access video and alarm information from remote retail branches as well as mobile devices. When a business grows, the future-proofed Blazer Express supports seamless integration with existing POS systems to provide data overlay, as well as People Counting, Heat Mapping, and ANPR – all to help owners with loss prevention and to improve business efficiency.

With so much to offer and being so easy to set up, the Blazer Express will quickly become the best video management station you have ever used!



BLAZER EXPRESS/16

16 CHANNEL BLAZER 1U 19" CASE



- Up to 16 channel IP video
- Up to 10 connected clients
- Up to 2 ANPR cameras
- Up to 15 cascading stations
- Up to 2x 4K Decoding capability
- Incoming bandwidth: 64Mbps
Outgoing bandwidth: 64Mbps
- Operation system: Windows Embedded System 7
- 2 HDDs connectable, up to 12TB
- 1-ch HDMI, 1-ch VGA output
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- Alarm in/out 4/2
- 4x USB 2.0 & 1x USB 3.0

PART NO.	QUICK REF.
Blazer Express/16	0788110

BLAZER EXPRESS/16/8P

16 CHANNEL BLAZER 1U 19" CASE



- Up to 16 channel IP video
- Up to 10 connected clients
- Up to 2 ANPR cameras
- Up to 15 cascading stations
- Up to 2x 4K Decoding capability
- Incoming bandwidth: 64Mbps
Outgoing bandwidth: 64Mbps
- Operation system: Windows Embedded System 7
- 2 HDDs connectable, up to 12TB
- 1-ch HDMI, 1-ch VGA output
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- Built-in 8 port PoE+ switch (Max. 120W)
- Alarm in/out 4/2
- 4x USB 2.0 & 1x USB 3.0

PART NO.	QUICK REF.
Blazer Express/16/8P	0788120

BLAZER EXPRESS/32

32 CHANNEL BLAZER 1.5U 19" CASE



- Up to 32 channel IP video
- Up to 10 connected clients
- Up to 2 ANPR cameras
- Up to 15 cascading stations
- Up to 2x 4K Decoding capability
- Incoming bandwidth: 128Mbps
Outgoing bandwidth: 64Mbps
- Operation system: Windows Embedded System 7
- 4 HDDs connectable, up to 24TB
- 1-ch HDMI, 1-ch VGA output
- 2 RJ-45 10/100/1000Mbps self-adaptive Ethernet interfaces
- Alarm in/out 4/2
- 4x USB 2.0 & 1x USB 3.0

PART NO.	QUICK REF.
Blazer Express/32	0788130

Encoders

DS-6701HWI

1 CHANNEL ENCODER



- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Up to WD1 real-time encoding
- Audio input/output: 1/1
- Connectable with network HDD in NAS, IP SAN mode
- IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, hkdDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, HIKCGL, netFilter
- Alarm in/out: 1/1
- Multiple PTZ protocols
- 1 RJ-45 10m/100Mbps adaptive Ethernet interface (PoE)
- 12VDC or PoE
- Dimension (W×D×H): 80×39×90mm

PART NO.	QUICK REF.
DS-6701HWI	0788140

DS-6704HWI

4 CHANNEL ENCODER



- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Up to WD1 real-time encoding
- Audio input/output: 4/1
- Connectable with network HDD in NAS, IP SAN mode
- IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, hkdDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, HIKCGL, netFilter
- Alarm in/out: 4/2
- Multiple PTZ protocols
- 1 RJ-45 10m/100Mbps adaptive Ethernet interface (PoE)
- 12VDC or PoE
- Dimension (W×D×H): 114×48×128mm

PART NO.	QUICK REF.
DS-6704HWI	0788150

DS-6708HWI

8 CHANNEL ENCODER



- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Up to WD1 real-time encoding
- Audio input/output: 8/1
- Connectable with network HDD in NAS, IP SAN mode
- IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, hkdDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, HIKCGL, netFilter
- Alarm in/out: 8/4
- Multiple PTZ protocols
- 1 RJ-45 10m/100m/1000Mbps adaptive Ethernet interface
- 12VDC
- Dimension (W×D×H): 315×45×200mm

PART NO.	QUICK REF.
DS-6708HWI	0788160

DS-6716HWI
16 CHANNEL ENCODER



- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Up to WD1 real-time encoding
- Audio input output: 16/1
- Connectable with network HDD in NAS, IP SAN mode
- IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, hkdDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, HIKCGI, netFilter
- Alarm in/out: 16/4
- Multiple PTZ protocols
- 1 RJ-45 10m/100m/1000Mbps adaptive Ethernet interface
- 12VDC
- Dimension (W×D×H): 440×45×274mm

PART NO.	QUICK REF.
DS-6716HWI	0788170

Decoders

DS-6401HDI-T
1 CHANNEL DECODER



- Audio output: 1-ch, RCA connector
- 8MP: 1-ch, 5MP: 2-ch, 3MP: 3-ch, 1080p: 4-ch, 720p: 8-ch, 4CIF: 16-ch
- 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output
- 1x RS-485
- 1x RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 12VDC
- Dimension (W×D×H): 220×180×45mm

PART NO.	QUICK REF.
DS-6401HDI-T	0788180

DS-6404HDI-T
4 CHANNEL DECODER



- Audio output: 4-ch, 1 DB15 interface
- 8MP: 2-ch, 5MP: 4-ch, 3MP: 6-ch, 1080p: 8-ch, 720p: 16-ch, 4CIF: 32-ch
- 4-ch DVI output, 2-ch CVBS output
- 1x RS-485
- 1x RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×340×70mm

PART NO.	QUICK REF.
DS-6404HDI-T	0783770

DS-6408HDI-T
8 CHANNEL DECODER



- Audio output: 8-ch, 1 DB15 interface
- 8MP: 4-ch, 5MP: 8-ch, 3MP: 12-ch, 1080p: 16-ch, 720p: 32-ch, 4CIF: 64-ch
- 8-ch DVI output, 4-ch CVBS output
- 1x RS-485
- 1x RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×340×70mm

PART NO.	QUICK REF.
DS-6408HDI-T	0788190

DS-6410HDI-T 10 CHANNEL DECODER



- Audio output: 16-ch, 2 DB15 interface
- 8MP: 5-ch, 5MP: 10-ch, 3MP: 14-ch, 1080p: 20-ch, 720p: 40-ch, 4CIF: 80-ch
- 10-ch DVI output, 5-ch CVBS output
- 1× RS-485
- 1× RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×340×88mm

DS-6412HDI-T 12 CHANNEL DECODER



- Audio output: 16-ch, 2 DB15 interface
- 8MP: 6-ch, 5MP: 12-ch, 3MP: 16-ch, 1080p: 24-ch, 720p: 48-ch, 4CIF: 90-ch
- 12-ch DVI output
- 6-ch CVBS output
- 1× RS-485
- 1× RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×340×88mm

DS-6416HDI-T 16 CHANNEL DECODER



- Audio output: 16-ch, 2 DB15 interface
- 8MP: 18-ch, 5MP: 16-ch, 3MP: 20-ch, 1080p: 32-ch, 720p: 64-ch, 4CIF: 100-ch
- 16-ch DVI output, 8-ch CVBS output
- 1× RS-485
- 1× RS-232
- Alarm input/output: 4/4
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×340×88mm

PART NO.	QUICK REF.
DS-6410HDI-T	0788200

PART NO.	QUICK REF.
DS-6412HDI-T	0788210

PART NO.	QUICK REF.
DS-6416HDI-T	0788220

DS-6901UDI 1 CHANNEL DECODER



- Audio input/output: 1/1
- 12MP@20ips: 2-ch, 8MP@30ips: 4-ch, 5MP@30ips: 6-ch, 3MP@30ips: 10-ch, 1080p@30ips: 16-ch
- 1-ch HDMI output, 1-ch VGA output, 1-ch CVBS output
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 1×10/100/1000Mbps self-adaptive Ethernet interface
- Power Supply: 12VDC
- Dimension (W×D×H): 220×148×45mm

DS-6904UDI 4 CHANNEL DECODER



- Audio input/output: 1/4, 1 DB15 interface
- 12MP@20ips: 4-ch, 8MP@30ips: 8-ch, 5MP@30ips: 12-ch, 3MP@30ips: 20-ch, 1080p@30ips: 32-ch
- 4-ch HDMI output, 4-ch VGA output, 2-ch CVBS output, 1 DB15 interface
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 2×10/100/1000Mbps self-adaptive management network interface, 2×10/100/1000Mbps self-adaptive Ethernet interface, 16×10m/100m self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×311×44.5mm

DS-6908UDI 8 CHANNEL DECODER



- Audio input/output: 1/8, 1 DB15 interface
- 12MP@20ips: 8-ch, 8MP@30ips: 16-ch, 5MP@30ips: 24-ch, 3MP@30ips: 40-ch, 1080p@30ips: 64-ch
- 8-ch HDMI output, 8-ch VGA output, 4-ch CVBS output, 1 DB15 interface
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 2×10/100/1000Mbps self-adaptive management network interface, 2×10/100/1000Mbps self-adaptive Ethernet interface, 16×10m/100m self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×311×44.5mm

PART NO.	QUICK REF.
DS-6901UDI	0788230

PART NO.	QUICK REF.
DS-6904UDI	0788240

PART NO.	QUICK REF.
DS-6908UDI	0788250

DS-6910UDI
10 CHANNEL DECODER



- Audio input/output: 1/10, 2 DB15 interface
- 12MP@20ips: 10-ch, 8MP@30ips: 20-ch, 5MP@30ips: 30-ch, 3MP@30ips: 50-ch, 1080p@30ips: 80-ch
- 10-ch HDMI output, 5-ch CVBS output, 2 DB15 interface
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 2×10/100/1000Mbps self-adaptive management network interface, 2× 10/100/1000 Mbps self-adaptive Ethernet interface, 16×10m/100m self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×311×80mm

DS-6912UDI
12 CHANNEL DECODER



- Audio input/output: 1/12, 2 DB15 interface
- 12MP@20ips: 12-ch, 8MP@30ips: 24-ch, 5MP@30ips: 36-ch, 3MP@30ips: 60-ch, 1080p@30ips: 96-ch
- 12-ch HDMI output, 6-ch CVBS output, 2 DB15 interface
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 2×10/100/1000Mbps self-adaptive management network interface, 2× 10/100/1000Mbps self-adaptive Ethernet interface, 16×10m/100m self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×311×80mm

DS-6916UDI
16 CHANNEL DECODER



- Audio input/output: 1/16, 2 DB15 interface
- 12MP@20ips: 16-ch, 8MP@30ips: 32-ch, 5MP@30ips: 48-ch, 3MP@30ips: 80-ch, 1080p@30ips: 128-ch
- 16-ch HDMI output, 8-ch CVBS output, 2 DB15 interface
- 1 RS-485
- 1 RS-232 (RJ 45)
- Alarm input/output: 8/8
- 2×10/100/1000Mbps self-adaptive management network interface, 2×10/100/1000 Mbps self-adaptive Ethernet interface, 16×10m/100m self-adaptive Ethernet interface
- Power Supply: 220VAC
- Dimension (W×D×H): 440×311×80mm

PART NO.	QUICK REF.
DS-6910UDI	0788260

PART NO.	QUICK REF.
DS-6912UDI	0788270

PART NO.	QUICK REF.
DS-6916UDI	0788280

DS-1004KI ANALOGUE KEYBOARD



- Power 12VDC
- Dimension (W×D×H): 433×163×43mm

DS-1005KI USB KEYBOARD FOR NVR/DVR/IVMS



- Compatible System: Windows XP/7/8/8.1
- 1-ch USB 2.0
- Power 5VDC via USB
- Dimension (W×D×H): 167×177.5×116mm

DS-1100KI NETWORK KEYBOARD



- 7" TFT LCD monitor with touch panel
- 1-ch Line in
- 1× RS-485
- 1× RS-232
- 1-ch Audio output
- 1 RJ-45 10m/100Mbps adaptive Ethernet interface (PoE)
- Power 12VDC

PART NO.	QUICK REF.
DS-1004KI	0783340

PART NO.	QUICK REF.
DS-1005KI	0783350

PART NO.	QUICK REF.
DS-1100KI	0783360

DS-1600KI TOUCH SCREEN NETWORK KEYBOARD



- 10.1" capacitive touchscreen
- PoE power supply
- Local decoding 2-ch at up to 1080p resolution, and up to 16-division window display
- 1x RS-232
- 1-ch Audio output
- 1 RJ-45 10m/100m/1000m self-adaptive Ethernet interface
- 1 HDMI output, 1 DVI output
- Power 12VDC/PoE

PART NO.	QUICK REF.
DS-1600KI	0788290

DS-D5019QE-B
19" LED MONITOR


- LED backlit technology with HD 1366×768
- Wide view angle: 90°(H)/65°(V)
- 3D comb filter
- 3D De-interlace
- 3D noise reduction
- Input: VGA
- VESA stand bracket

DS-D5022QE-B
22" LED MONITOR


- LED backlit technology with full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- 3D comb filter
- 3D De-interlace
- 3D noise reduction
- Multiple inputs: HDMI, VGA, audio in
- Built-in speaker
- VESA stand bracket

DS-D5022FC
21.5" LED MONITOR


- LED backlit technology with full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction
- Multiple inputs: HDMI, VGA, BNC, audio in
- Multiple outputs: BNC, audio output
- Built-in speaker
- External video play via USB port
- Highly reliable components for 24/7 working
- VESA stand bracket

PART NO.	QUICK REF.
DS-D5019QE-B	0789220

PART NO.	QUICK REF.
DS-D5022QE-B	0789230

PART NO.	QUICK REF.
DS-D5022FC	0789240

DS-D5032FC
32" LED MONITOR


- Support 8bit/10bit 2-ch LVDS (1920×1080) HD display
- True colour OSD and user-friendly operation menu
- 1 channel HDMI 1.3 input interface, support HDCP 1.2
- Adopt 3D noise reduction technology
- Supports high definition JPEG decoding
- Programmable 12-bit RGB gamma correction technology
- Supports software spread-spectrum technology to reduce EMI radiation
- Adopt Mstar ACE-5 auto colour and image enhancement engine, improve image contrast, detail and edge

DS-D2046NH-C
46" LCD DISPLAY UNIT


- LED Direct-lit backlight with uniform brightness and no boundary shadow
- Resolution: 1920×1080
- High display resolution and delicate image with rich colour
- High definition, high brightness, high colour gamut
- DID LCD screen with 178° wide angle
- Large display area, light weight
- Longer display lifespan
- Multiple joining methods, applicable for various scenes
- Ultra-slim bi-side seam, only 3.5mm wide between neighbouring units

DS-D2055NH-B
55" LCD DISPLAY UNIT


- LED Direct-lit backlight with uniform brightness and no boundary shadow
- Resolution: 1920×1080
- High display resolution and delicate image with rich colour
- High definition, high brightness, high colour gamut
- DID LCD screen with 178° wide angle
- Large display area, light weight
- Longer display lifespan
- Multiple joining methods, applicable for various scenes
- Ultra-slim bi-side seam, only 3.5mm wide between neighbouring units

PART NO.	QUICK REF.
DS-D5032FC	0789250

PART NO.	QUICK REF.
DS-D2046NH-C	0789260

PART NO.	QUICK REF.
DS-D2055NH-B	0789270

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com



SEEING IS COMMUNICATING

Hikvision's Visual Intercom System extends surveillance capabilities, adding a level of safety to a user's home. It creates a hub for emergency responses. It adds an access control dimension to reinforce a sense of safety in the home or workplace. And Hikvision's echo-cancellation technology ensures high quality voice transmission, providing an exceptional user experience. All this and more can be easily managed with a mobile app.

The Visual Intercom System from Hikvision makes communication more personal, more pleasant and more technologically advanced than ever before.



DS-KD8102-V
DOOR STATION



- 3.5" Capacitive Touch Key 1.3MP Door Station, plastic
- 3.5" Colourful TFT LCD, display resolution: 480×320
- Camera resolution: HD 720p, 25ips (P)/30ips (N)
- 10m/100m/1000m self-adaptive Ethernet
- Wiegand & RS-485, 8-ch alarm input, 4-ch alarm output, USB 2.0
- IP65
- 12VDC
- Visible light supplement

DS-KD8002-VM
DOOR STATION



- 3.5" Physical Touch Key 1.3MP Door Station, aluminium alloy
- 3.5" Colourful TFT LCD, display resolution: 480×320
- Camera resolution: HD 720p, 25ips (P)/30ips (N)
- 10m/100m/1000m self-adaptive Ethernet
- Wiegand & RS-485, 8-ch alarm input, 4-ch alarm output, USB 2.0
- IP65
- 12VDC
- Visible light supplement

DS-KV8102-IM
VILLA DOOR STATION



- 1.3MP Villa Door Station, aluminium alloy
- Camera resolution: HD 720p, 25ips (P)
- 10m/100m self-adaptive Ethernet
- RS-485, 4-ch alarm input, 1-ch alarm output
- IP65
- 12VDC
- 1-ch Indoor Station access
- IR supplement

PART NO.	QUICK REF.
DS-KD8102-V	0786030

PART NO.	QUICK REF.
DS-KD8002-VM	0786040

PART NO.	QUICK REF.
DS-KV8102-IM	0786060

DS-KV8202-IM
VILLA DOOR STATION



- 1.3MP Villa Door Station, aluminium alloy
- Camera resolution: HD 720p, 25ips (P)
- 10m/100m self-adaptive Ethernet
- RS-485, 4-ch alarm input, 1-ch alarm output
- IP65
- 12VDC
- 2-ch Indoor Station access
- IR supplement

DS-KV8402-IM
VILLA DOOR STATION



- 1.3MP Villa Door Station, aluminium alloy
- Camera resolution: HD 720p, 25ips (P)
- 10m/100m self-adaptive Ethernet
- RS-485, 4-ch alarm input, 1-ch alarm output
- IP65
- 12VDC
- 4-ch Indoor Station access
- IR supplement

DS-KV8102-IP
VILLA DOOR STATION



- 1.3MP Villa Door Station, Plastic
- Camera resolution: HD 720p, 25ips (P)
- 10m/100m Self-adaptive Ethernet
- RS-485, 4-ch alarm input, 1-ch alarm output
- IP65
- 12VDC
- 1-ch Indoor Station access
- IR supplement

PART NO.	QUICK REF.
DS-KV8202-IM	0786070

PART NO.	QUICK REF.
DS-KV8402-IM	0786080

PART NO.	QUICK REF.
DS-KV8102-IP	0786090

DS-KH8301-WT INDOOR STATION



- 0.3MP 7" Touch-Screen Indoor Station
- 7" Colourful TFT LCD, display resolution: 1024×600
- Camera resolution: 640×480; Mechanical switch
- 10/100Mbps Ethernet
- Wi-Fi 802.11b/g/n
- 8-ch alarm input
- Supports SD card
- 12VDC

DS-KAD606 DISTRIBUTOR



- Built-in voltage-stabilised power
- 8x100Mbps ports (6-ch supporting network cable powering and 2-ch cascading LAN interfaces)
- Suitable for Indoor Station and Villa Door Station

DS-KAW50-1 POWER SUPPLY



- Power supply for Door Station and Villa Door Station
- Output: 12VDC, 4.2A

PART NO.	QUICK REF.	PART NO.	QUICK REF.	PART NO.	QUICK REF.
DS-KH8301-WT	0786110	DS-KAD606	0786120	DS-KAW50-1	0786130

DS-1227ZJ IN-CEILING MOUNT



- Hik white
- Aluminium alloy & ABS Plastic
- $\Phi 210 \times 90 \text{mm}$
- 540g

PART NO.	QUICK REF.
DS-1227ZJ	0784070

DS-1240ZJ INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- $\Phi 145 \times 63 \text{mm}$
- 440g

PART NO.	QUICK REF.
DS-1240ZJ	0788300

DS-1241ZJ IN-CEILING MOUNT



- Hik white
- Aluminium alloy
- $\Phi 200 \times 26.8 \text{mm}$
- 300g

PART NO.	QUICK REF.
DS-1241ZJ	0788310

DS-1249ZJ IN-CEILING MOUNT



- Hik white
- ABS plastic
- $\Phi 169.4 \times 14.6 \text{mm}$
- 60g

PART NO.	QUICK REF.
DS-1249ZJ	0788320

DS-1250ZJ RAIN SHADE



- Hik white
- Composite Fibre
- $264.7 \times 152 \times 189.6 \text{mm}$
- 199g

PART NO.	QUICK REF.
DS-1250ZJ	0788330

DS-1253ZJ-L RAIN SHADE



- Hik white
- Composite Fibre
- $\Phi 225.1 \times 98 \text{mm}$
- 198g
- Match up with wall mount (DS-1273ZJ-140)

PART NO.	QUICK REF.
DS-1253ZJ-L	0788340

DS-1258ZJ WALL MOUNT



- Hik white
- ABS plastic
- $120 \times 111 \times 161.5 \text{mm}$
- 200g

PART NO.	QUICK REF.
DS-1258ZJ	0788350

DS-1259ZJ INCLINED CEILING MOUNT



- Hik white
- ABS Plastic
- $\Phi 111 \times 39.2 \text{mm}$
- 200g

PART NO.	QUICK REF.
DS-1259ZJ	0788360

DS-1260ZJ JUNCTION BOX



- Hik white
- Aluminium alloy
- $\Phi 105 \text{mm}$

PART NO.	QUICK REF.
DS-1260ZJ	0783370

DS-1271ZJ-110 PENDANT MOUNT



- Hik white
- Aluminium alloy
- $\Phi 150 \times 560 \text{mm}$
- 1900g

PART NO.	QUICK REF.
DS-1271ZJ-110	0783380

DS-1271ZJ-120 PENDANT MOUNT



- Hik white
- Aluminium alloy
- $\Phi 150 \times 573 \text{mm}$
- 1290g

PART NO.	QUICK REF.
DS-1271ZJ-120	0784090

DS-1271ZJ-130 PENDANT MOUNT



- Hik white
- Aluminium alloy
- $\Phi 150 \times 565 \text{mm}$
- 1900g

29 MM	QUICK REF.
DS-1271ZJ-130	0784100

DS-1271ZJ-135
PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø136×565mm
- 1350g

PART NO.	QUICK REF.
DS-1271ZJ-135	0788380

DS-1271ZJ-140
PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø150×565mm
- 1900g

PART NO.	QUICK REF.
DS-1271ZJ-140	0784110

DS-1271ZJ-DM25
PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø149.5×555mm
- 1930g

PART NO.	QUICK REF.
DS-1271ZJ-DM25	0788390

DS-1271ZJ-DM26
PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø185×676mm
- 2150g

PART NO.	QUICK REF.
DS-1271ZJ-DM26	0788400

DS-1271ZJ-DM30
PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø209×650mm
- 2050g

PART NO.	QUICK REF.
DS-1271ZJ-DM30	0788410

DS-1272ZJ-110
WALL MOUNT



- Hik white
- Aluminium alloy
- 120×122×169mm
- 420g

PART NO.	QUICK REF.
DS-1272ZJ-110	0783390

DS-1272ZJ-110B
WALL MOUNT



- Hik white
- Aluminium alloy
- With junction box
- 123×180×227.8mm
- 1205g

PART NO.	QUICK REF.
DS-1272ZJ-110B	0788420

DS-1272ZJ-110-TRS
WALL MOUNT



- Hik white
- Aluminium alloy
- 120×122×169mm
- 420g

PART NO.	QUICK REF.
DS-1272ZJ-110-TRS	0788430

DS-1272ZJ-120
WALL MOUNT



- Hik white
- Aluminium alloy
- 120×122×173.5mm
- 430g

PART NO.	QUICK REF.
DS-1272ZJ-120	0784120

DS-1272ZJ-120B
WALL MOUNT



- Hik white
- Aluminium alloy
- With junction box
- 123×180×223mm
- 1225g

PART NO.	QUICK REF.
DS-1272ZJ-120B	0788440

DS-1273ZJ-130
WALL MOUNT



- Hik white
- Aluminium alloy
- 132×183.5×228.5mm
- 690g

PART NO.	QUICK REF.
DS-1273ZJ-130	0784130

DS-1273ZJ-130B
WALL MOUNT



- Hik white
- Aluminium alloy
- With junction box
- 132×243×288.5mm
- 1475g

PART NO.	QUICK REF.
DS-1273ZJ-130B	0788450

DS-1273ZJ-130-TRL WALL MOUNT



- Hik white
- Aluminium alloy
- 131×183.5×228.5mm
- 890g

PART NO.	QUICK REF.
DS-1273ZJ-130-TRL	0784140

DS-1273ZJ-135 WALL MOUNT



- Hik white
- Aluminium alloy
- 136×183.5×230mm
- 704g

PART NO.	QUICK REF.
DS-1273ZJ-135	0784150

DS-1273ZJ-135B WALL MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy
- With junction box
- 136×243×290mm
- 1490g

PART NO.	QUICK REF.
DS-1273ZJ-135B	0788730

DS-1273ZJ-140 WALL MOUNT



- Hik white
- Aluminium alloy
- 140×183.5×232mm
- 703g

PART NO.	QUICK REF.
DS-1273ZJ-140	0784160

DS-1273ZJ-140B WALL MOUNT



- Hik white
- Aluminium alloy
- With junction box
- 140×243×292mm
- 1488g

PART NO.	QUICK REF.
DS-1273ZJ-140B	0788740

DS-1273ZJ-160 WALL MOUNT



- Hik white
- Aluminium alloy
- 160×183.5×243mm
- 845g

PART NO.	QUICK REF.
DS-1273ZJ-160	0788750

DS-1273ZJ-160B WALL MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy
- 160×243×303mm
- 1630g

PART NO.	QUICK REF.
DS-1273ZJ-160B	0788760

DS-1273ZJ-DM25 WALL MOUNT



- Hik white
- Aluminium alloy
- 183.5×164×231.7mm
- 900g

PART NO.	QUICK REF.
DS-1273ZJ-DM25	0788770

DS-1273ZJ-DM26 WALL MOUNT



- Hik white
- Aluminium alloy
- 255×225.7×185mm
- 1550g

PART NO.	QUICK REF.
DS-1273ZJ-DM26	0784170

DS-1273ZJ-DM26-B WALL MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy
- 314.5×260×184.9mm
- 2050g

PART NO.	QUICK REF.
DS-1273ZJ-DM26-B	0788780

DS-1273ZJ-DM30-B WALL MOUNT



- Hik white
- Aluminium alloy
- Ø209×243×326mm
- 2500g

PART NO.	QUICK REF.
DS-1273ZJ-DM30-B	0788800

DS-1275ZJ VERTICAL POLE MOUNT



- Hik white
- Steel (mounting board) & Stainless Steel (clamp)
- 127×46×250mm
- Diameter of clamp: Ø67-127mm
- 1205g

PART NO.	QUICK REF.
DS-1275ZJ	0783400

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-1275ZJ-4626 VERTICAL POLE MOUNT



- Steel (mounting board) & Stainless Steel (clamp)
- 127×46×250mm
- 1235g

PART NO.	QUICK REF.
DS-1275ZJ-4626	0788810

DS-1276ZJ CORNER MOUNT



- Hik white
- Steel
- 126×105×250mm
- 2280g
- Match up with wall mount (DS-1293ZJ)

PART NO.	QUICK REF.
DS-1276ZJ	0784180

DS-1280ZJ-DM18 JUNCTION BOX



- Hik white
- Aluminium alloy
- Ø115.4×43.8mm
- 450g

PART NO.	QUICK REF.
DS-1280ZJ-DM18	0783410

DS-1280ZJ-DM21 JUNCTION BOX



- Hik white
- Aluminium alloy
- Ø137 mm × 42 mm
- 280g

PART NO.	QUICK REF.
DS-1280ZJ-DM21	0784190

DS-1280ZJ-DM25 JUNCTION BOX



- Hik white
- Aluminium alloy
- 178.5×164×41mm
- 340g

PART NO.	QUICK REF.
DS-1280ZJ-DM25	0788820

DS-1280ZJ-DM26 JUNCTION BOX



- Hik white
- Aluminium alloy
- Ø165×65mm
- 466g

PART NO.	QUICK REF.
DS-1280ZJ-DM26	0784200

DS-1280ZJ-M JUNCTION BOX



- Hik white
- Aluminium alloy
- Ø157×185×51.5mm
- 621g

PART NO.	QUICK REF.
DS-1280ZJ-M	0783420

DS-1280ZJ-S JUNCTION BOX



- Hik white
- Aluminium alloy
- Ø137 x 53.4x 164.8mm
- 527g

PART NO.	QUICK REF.
DS-1280ZJ-S	0783430

DS-1280ZJ-XS JUNCTION BOX



- Hik white
- Aluminium Alloy
- Ø100x43.2x129mm
- 320g

PART NO.	QUICK REF.
DS-1280ZJ-XS	0783440

DS-1281ZJ-DM23 INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- Ø136×48mm
- 245g

PART NO.	QUICK REF.
DS-1281ZJ-DM23	0788830


DS-1281ZJ-DM25 INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- 157.1×164×45.5mm
- 300g

PART NO.	QUICK REF.
DS-1281ZJ-DM25	0788840

DS-1281ZJ-DM26 INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- Ø165×75.7mm
- 425g

PART NO.	QUICK REF.
DS-1281ZJ-DM26	0788850

DS-1281ZJ-M INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- 157×165.7×61.8mm
- 586g

PART NO.	QUICK REF.
DS-1281ZJ-M	0788860

DS-1281ZJ-S INCLINED CEILING MOUNT



- Hik white
- Aluminium alloy
- 137×56.5×147mm
- 472g

PART NO.	QUICK REF.
DS-1281ZJ-S	0788870

DS-1282ZJ-DM (MINI) GANG BOX



- Hik white
- Plastic
- Ø120 mm

PART NO.	QUICK REF.
DS-1282ZJ-DM(MINI)	0788880

DS-1283ZJ THREE AXIS ADJUSTMENT



- Hik white
- Aluminium alloy
- 167.5×167.5×48.7mm

PART NO.	QUICK REF.
DS-1283ZJ	0788890

DS-1290ZJ-BL CLAMP BRACKET



- Black
- Plastic
- 90×70×22mm

PART NO.	QUICK REF.
DS-1290ZJ-BL	0788900

DS-1291ZJ-BL DESKTOP/PENDANT MOUNT



- Black
- Plastic
- 87×73×73mm

PART NO.	QUICK REF.
DS-1291ZJ-BL	0788910

DS-1294ZJ WALL MOUNT



- Hik white
- Toughened Plastic
- 223.9×80×125.8mm
- 450g

PART NO.	QUICK REF.
DS-1294ZJ	0788920

DS-1297ZJ PENDANT MOUNT (EXTENDABLE)



- Hik white
- Aluminium alloy
- Height 1000-2000mm

PART NO.	QUICK REF.
DS-1297ZJ	0788930

DS-1602ZJ WALL MOUNT (LONG ARM)



- Hik white
- Aluminium alloy
- 97.3×182.6×306.3mm
- 1050g

PART NO.	QUICK REF.
DS-1602ZJ	0783450

DS-1602ZJ-BOX WALL MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy
- 182.6×104×311.1mm
- 3230g

PART NO.	QUICK REF.
DS-1602ZJ-BOX	0788950

DS-1602ZJ-CORNER CORNER MOUNT



- Hik white
- Aluminium alloy
- 176.8×194×417.8mm
- 2809g

PART NO.	QUICK REF.
DS-1602ZJ-CORNER	0783460

DS-1602ZJ-POLE VERTICAL POLE MOUNT



- Hik white
- Aluminium alloy
- 117×194×451.3mm
- 2040g

PART NO.	QUICK REF.
DS-1602ZJ-POLE	0784210

Hikvision products are available through your local authorised distributor **Norbain**

For Orders Call: Tel. +44 (0) 118 912 5000 - Fax +44 (0) 118 912 5001 - Email: sales@norbain.com - Web: www.norbain.com

DS-1602ZJ-BOX-CORNER WALL CORNER MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy & steel
- 255.5×314×546.4mm
- 8396g

PART NO.	QUICK REF.
DS-1602ZJ-BOX-CORNER	0076320

DS-1602ZJ-BOX-POLE VERTICAL POLE MOUNT WITH JUNCTION BOX



- Hik white
- Aluminium alloy & steel
- 209.7×314×600.8mm
- 6840g

PART NO.	QUICK REF.
DS-1602ZJ-BOX-POLE	0788970

DS-1603ZJ WALL MOUNT



- Hik white
- Aluminium alloy
- 98×182×362mm

PART NO.	QUICK REF.
DS-1603ZJ	0788980

DS-1618ZJ WALL MOUNT (SHORT ARM)



- Hik white
- Aluminium alloy
- 110×145×189mm
- 550g

PART NO.	QUICK REF.
DS-1618ZJ	0788990

DS-1619ZJ SWAN NECK MOUNT



- Hik white
- Aluminium alloy
- 455.2×130.4×841.5mm

PART NO.	QUICK REF.
DS-1619ZJ	0783470

DS-1660ZJ PARAPET WALL MOUNT



- Hik white
- Aluminium alloy
- 180×950×800mm
- 2900g

PART NO.	QUICK REF.
DS-1660ZJ	0789000

DS-1661ZJ PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø116.5×200mm
- 600g

PART NO.	QUICK REF.
DS-1661ZJ	0789010

DS-1662ZJ PENDANT MOUNT



- Hik white
- Aluminium alloy
- Ø116.5×500mm
- 960g

PART NO.	QUICK REF.
DS-1662ZJ	0784220

DS-1663ZJ CEILING MOUNT



- Hik white
- Aluminium alloy
- Ø116.5×57mm
- 380g

PART NO.	QUICK REF.
DS-1663ZJ	0784230

DS-1667ZJ EXTENDABLE POLE FOR PENDANT MOUNT



- Hik white
- Galvanised steel pipe
- Height: 1500-2500mm

PART NO.	QUICK REF.
DS-1667ZJ	0789020

DS-1668ZJ PENDANT MOUNT



- Hik white
- Steel
- Ø115×58mm
- 620g

PART NO.	QUICK REF.
DS-1668ZJ	0789030

DS-1668ZJ(20) PENDANT MOUNT



- Hik white
- Steel
- Ø115×200mm
- 1150g

PART NO.	QUICK REF.
DS-1668ZJ (20)	0789040

DS-1H05-T ETHERNET OVER COAX (TRANSMITTER)



- Input: 1 RJ45 interface and BNC
- Output: 1x BNC
- Up to 1,500 feet with RG6/U cable
- Dimension (W×D×H): 80×96×27mm
- Power 12VDC, 5W

DS-1H05-R ETHERNET OVER COAX (RECEIVER)



- Input: 1x BNC
- Output: 1 RJ45 interface and BNC
- Up to 1,500 feet with RG6/U cable
- Dimension (W×D×H): 80×96×27mm
- Power 12VDC, 5W

DS-1H18 TURBO VIDEO BALUNS



- Bandwidth: ODC to 60MHz
- Distance: 200m
- Impedance: 75Ω to 100Ω

DS-UTF16GI-L1 16GB MICRO SD CARD



- Class 10; 25MB/s read and 20MB/s write
- Storage Temperature: -25°C to 85°C
- Waterproof, shock proof, X-ray proof
- Operation Temperature: -0°C to 70°C
- Dimension (W×D×H): 14.99×10.92×1.02mm

PART NO.	QUICK REF.
DS-1H05-T	0788460

PART NO.	QUICK REF.
DS-1H05-R	0788470

PART NO.	QUICK REF.
DS-1H18	0785340

PART NO.	QUICK REF.
DS-UTF16GI-L1	0788480

DS-UTF32GI-L1 32GB MICRO SD CARD



- Class 10; 25MB/s read and 20MB/s write
- Storage Temperature: -25°C to 85°C
- Waterproof, shock proof, X-ray proof
- Operation Temperature: -0°C to 70°C
- Dimension (W×D×H): 14.99×10.92×1.02mm

DS-UTF64GI-L1 64GB MICRO SD CARD



- Class 10; 25MB/s read and 20MB/s write
- Storage Temperature: -25°C to 85°C
- Waterproof, shock proof, X-ray proof
- Operation Temperature: -0°C to 70°C
- Dimension (W×D×H): 14.99×10.92×1.02mm

DS-UTF128GI-L1 128GB MICRO SD CARD



- Class 10; 25MB/s read and 20MB/s write
- Storage Temperature: -25°C to 85°C
- Waterproof, shock proof, X-ray proof
- Operation Temperature: -0°C to 70°C
- Dimension (W×D×H): 14.99×10.92×1.02mm

POE INJECTOR POE INJECTOR TO POWER ON THE PTZ CAMERA



- Single port PoE midspan
- Max. 60W

PART NO.	QUICK REF.
DS-UTF32GI-L1	0788490

PART NO.	QUICK REF.
DS-UTF64GI-L1	0788500

PART NO.	QUICK REF.
DS-UTF128GI-L1	0788510

PART NO.	QUICK REF.
POE INJECTOR	0788520

**HIKVISION**

HIKVISION HCSA TECHNICAL TRAINING COURSE - **FREE**

Join us at the Hikvision UK Training Academy, Uxbridge, UK

Hikvision, the world's leading manufacturer of surveillance equipment, from CCTV to IT technology, has gained a lot of experience along the way and would love to share it with you. Hikvision wants to improve industry standards by offering free, HCSA accredited professional video surveillance certification to validate your existing video expertise. The Hikvision HCSA certification programme is open to our UK customers and partners.

HCSA (Hikvision Certified Security & Protection Associate) focuses on the basic and essential operation & maintenance of Hikvision security devices. It is designed for security technical engineers who have worked in the security industry for several years and already understand the basics of CCTV systems.

There will be a 45 minute test at the end of the training. Those who pass the test will be issued a Hikvision HCSA certificate.

For more training info, please speak to your Norbain account manager or email training.uk@hikvision.com



Hikvision UK
4 The Square,
Stockley Park, Uxbridge, UB11 1ET
Tel: 01628 902140
sales.uk@hikvision.com
support.uk@hikvision.com

www.hikvision.com

To experience Norbain's service levels first-hand,
get in touch using the contact details below:



NORTH

Seecom Technology Centre
Wyrefields, Poulton le Fylde
Lancashire
FY6 8JX

 **01253 894 488**

SOUTH

210 Wharfedale Road
Winnersh, Wokingham
Berkshire
RG41 5TP

 **0118 912 5000**



EMAIL:
info@norbain.com



WEB:
www.norbain.com



OPENING HOURS:
8.30am to 6.00pm